Tervetuloa O-johtaviin

Olemme ammatillinen PCB-valmistaja, jossa on yli kymmenen vuoden kokemuksia. Tuotteiden valikoima- yhden, kahden puolen, monikerroksinen PCB, joustavat PCB ja MCPCB.We voivat tarjota nopean prototyyppipalvelu - S / S 24 tuntia, 4-8layers vuonna 48-96 työ- tuntia tuotantoaikaa.

Kuparilevyn reikiä vähintään 0,025 avg, .020 min .. Reiät eivät ehkä ole kytkettynä

Pakkaus väritöntä läpinäkyvällä kuplakalvolla, 25 kpl / laukku, laita kuivausmerkille, laita kosteuden indikaattorikortti yläreunaan

Napsauta näitä lisätietoja:Moottorin teho-moduuli Valmistaja Kiina

Tuotteen Kuvaus

Pikatiedot

Lähtöisin	Guang Dong, Kiina (Manner)	Tuotenimi	O-johtava
Mallinumero	Power Bank PCB: n kokoonpano PCBA-valmistaja	Pohjamateriaalia	FR-4, alumiini
Pinnan viimeistely	Upotus kulta, OSP, Lead Free Hasl	Kuparipaksuus	0.5oz-5oz
sovellettava	LED, matkapuhelin, ilmastointilaitteet, pesukoneet	Paksuus	0,1-5mm
merkki	Teollisuuden ohjaus PCB	Min. Reiän koko	0,2 mm
sertifikaatit	ISO9001, UL, ROHS, SGS	Min. Viivan leveys	0,2 mm
Desiule tyyppi	Asiakkaan vaatimus	Min. Riviväli	0,2 mm
väri-	Sininen, punainen, vihreä, musta.Yellow	hinta	$ 0.1 - 10 dollaria
koko	0,01m3-10m3	Moq	10 kpl
paino	0,01 kg -5kg	Q / CTN	10PCS-100PCS

Pakkaus ja toimitus

Pakkaustiedot:	16 vuotta ammatillinen OEM PCB Board Valmistaja
Toimitustiedot:	7-12 päivää

Tuotteen Kuvaus

16 vuotta ammatillinen OEM PCB-kortin valmistus

tuote	2014		2015 ~ 2016		2017 ~ 2018	
	Määrä	Näyte	Määrä	Näyte	Määrä	Näyte
Kerroslaskenta	32	42	38	44	42	48
Min Line / Space (µm)	50/50	40/45	40/45	40/40	35/40	35/35
Min porausreikä Halkaisija (mm)	0,15	0,10	0,15	0,10	0,15	0,10

Kuvasuhde pth	14: 1	16: 1	16: 1	18: 1	18: 1	20: 1
N + c + n	4 + C + 4	5 + C + 5	5 + C + 5	6 + C + 6	5 + C + 5	6 + C + 6
Kaikki kerroksen yhteenliittäminen	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6
Levyn täyttö	JOO	-	JOO	-	JOO	-
Min. Core-paksuus (sulje kupari) (µm)	50	40	40	30	40	30
Min. Laserporaushalkaisija (µm)	75	65	65	50	50	40
Kautta haudattu reikä / pinottu kautta	JOO	-	JOO	-	JOO	-
Materiaali	FR4, Megtron, Nelco, Rogers, Raskas kupari jne.					
Sulautettu kondensaattori PCB	JOO	-	JOO	-	JOO	-
Pintaprosessi	Lyijytön HASL, ENIG, OSP, upotus hopea, upotus tina, Flash kulta, kulta sormi, valikoiva kova kultapinnoitus, Peelable juotosmaski, hiili muste					

HDI PCB painettu piirilevy, PCB LED-TV: n valmistajille Kiina

Tiimimme

O-LEADING
To Be Reliable, To Be Valuable

Sertifikaatit

Quality Management System Certificate

This is to certify that
(Organization Code Certificate : 61691591-000-07-16-8)

O-LEADING SUPPLY CHAIN (HK) CO.,LIMITED

ROOM 603D, 6/F HANG PONT COMMERCIAL BUILDING, 31 TONKIN ST., CHEUNG SHA WAN, KL, HK

has been established the quality management system meeting the requirements of standard

GB/T19001-2008/ISO9001:2008

Scope:

Certification Address: Room 1313, Fortune Building, Nanheng West Road, Huiyang District, Huizhou, Guangdong, China

Certification Activities: Sales and services of printed circuit boards

Certificate No.: 51816Q01163R0S

Issued Date : 2016-11-17 **Valid to :** 2018-09-15

Initial Issued Date : 2016-11-17 **Renewal Date :** ***

GM

CICC INSPECTION CERTIFICATION

CICC CERTIFICATION 嘉泰认证

QUALITY MANAGEMENT SYSTEM CERTIFICATE

Certificate No: 18118Q10347R0S

We hereby certify that

O-LEADING SUPPLY CHAIN(HK) CO.,LIMITED

Credit No: 61691591-000-07-17-2

Registration Add:ROOM 603D,6/F HANG PONT COMMERCIAL BUILDING,31 TONKIN ST,CHEUNG SHA WAN,KL,HK

Business Add:1313,Floor 13,Fortune Building,Danshui Town,Huiyang District, Huizhou,Guangdong,China

Has implemented and maintains a **Quality Management System**
Which fulfils the requirements of the following standards
GB/T19001-2016 idt ISO9001:2015

Scope of certification

Sales of printed circuit boards

Initial Issuance period: February 27, 2018
This certificate is valid during: February 27, 2018 — February 26, 2021
This certificate is invalid without CICC qualified label in the following period

First supervision and audit	Qualified mark	Second supervision and audit	Qualified mark

The certification registration scope doesn't include those product/service scopes which fail to be covered by the relevant effective administration permission and qualification permission regulated by the state.
The effectiveness of this certificate shall be validated by annual surveillance audit of CICC the certificate shall be valid that used together with the surveillance audit conclusion.
The related information of this certification can be searched at the portal
On the site of company www.cicc-hk.com

CICC CERTIFICATION IAF CNAS

2017/2/6 ZPMV2.E490354 - Wiring, Printed - Component

UL ONLINE CERTIFICATIONS DIRECTORY

ZPMV2.E490354
Wiring, Printed - Component

For enhanced search functionality, please visit UL's iQ™ Family of Databases.
Click on a product designation for complete information.
Page Bottom

Wiring, Printed - Component

See General Information for Wiring, Printed - Components

O-LEADING SUPPLY CHAIN CO LIMITED E490354
Fortune Building, Nanheng West Road
Room 1313
Huizhou, Guangdong 516211, CHINA

	Cond Width				Max			Max			
		Min	Cond	SS/	Area	Solder		Oper		Meets	C
	Min	Edge	Thk	DS/	Diam	Limits		Temp	Flame	UL796	T
Type	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
Multilayer (mass laminate) printed wiring boards.											
O-LEADING-401											
	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	130	V-0	-	-
O-LEADING-407											
	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.7 (0.4)	260	10	130	V-0	All	-
Multilayer printed wiring boards.											
O-LEADING-408											
	0.125 (0.005)	0.125 (0.005)	12 (0.47) Int:135	DS	50.8 (2.0)	260	20	130	V-0	All	*
Single layer printed wiring boards.											
O-LEADING-002											
	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	All	-
O-LEADING-003											
	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	130	V-0	▲	-
O-LEADING-033											
	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	All	-
O-LEADING-205											
	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.8 (2.7)	260	10	130	V-0	All	-
O-LEADING-206											
	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	All	-

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.
Last Updated on 2017-01-27

Questions? Print this page Terms of Use Page Top

SGS

Test Report No. CANEC1805164701 Date: 03 Apr 2018 Page 2 of 6

Test Results :

Test Part Description :

Specimen No.	SGS Sample ID	Description
SN1	CAN18-051647.001	Green "PCB"

Remarks :

(1) 1 mg/kg = 1 ppm = 0.0001%
(2) MDL = Method Detection Limit
(3) ND = Not Detected (< MDL)
(4) "-" = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method : With reference to IEC 62321-4:2013+A1:2017, IEC62321-5:2013, IEC62321-7-2:2017 , IEC 62321-6:2015 and IEC62321-8:2017, analyzed by ICP-OES , UV-Vis and GC-MS .

Test Item(s)	Limit	Unit	MDL	001
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	9
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (CrVI)	1,000	mg/kg	8	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tribromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND
Dibromodiphenyl ether	-	mg/kg	5	ND
Tribromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/terms_and_conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this report refer only to the sample(s) tested.
Attention: To verify authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
Member of the SGS Group (SGS SA)

Pakkaus ja toimitus

Pakkaustiedot	16 vuotta ammatillinen OEM PCB Board Valmistaja
Toimitustiedot	7-12 päivää

(Golden Finger Board Toimittaja)

FAQ

1. Miten O-johtava takaa laadun?
Korkealaatuinen standardi saavutetaan seuraavalla tavalla.
1. Prosessia valvotaan tiukasti ISO 9001: 2008 -standardeissa.
2. OHJELMISTON KÄYTTÖ Tuotantoprosessin hallinnassa
3.Tate-of-of-art-testauslaitteet ja työkalut. Esimerkiksi. Flying Probe, Röntgentarkastus, AOI (automaattinen optinen tarkastaja) ja tieto- ja viestintätekniikka (piiri testaus).
4.ded laadunvarmistusryhmä vika-tapausanalyysiprosessi
5.Kondiininen henkilöstön koulutus ja koulutus

2. Miten O-johtava pitää hintasi kilpailukykyinen?
Viime vuosikymmenen aikana monien raaka-aineiden (esim. Kupari, kemikaalit) hinnat olivat kaksinkertaistuneet, kolminkertaiset tai nelinkertaistuivat; Kiinan valuutta RMB oli arvostettu 31% Yhdysvaltain dollareina; Ja työvoimakustannukset kasvoivat myös merkittävästi. O-johtava on kuitenkin pitänyt hinnoittelumme tasaisesti. Tämä omistaa kokonaan innovaatioihimme kustannusten vähentämisessä, jätteiden välttämiseksi ja tehokkuuden parantamiseksi. Hintamme ovat erittäin kilpailukykyisiä teollisuudessa samalla laatutasolla.
Uskomme win-win-kumppanuuteen asiakkaidemme kanssa. Yhteistyömme hyödyllisesti hyödyttävä, jos voimme tarjota sinulle reunan kustannuksella ja laadulla.

3. Millaisia levyt voivat O-johtava prosessi?
Yleiset FR4, korkean Tg- ja Halogeeniton levyt, Rogers, Arlon, Telfon, Alumiini / kuparipohjaiset levyt, PI jne.

4. Mitä tietoja tarvitaan PCB-tuotantoon?
On parasta tarjota tietoja Gerber 274-X -muodossa. Lisäksi CAM350, CAD, Protel 99se, tyynyjä, DXP ja EAGLE voidaan käsitellä.

5. Mikä on tyypillinen prosessivirta monikerrokselle PCB?
Materiaalin leikkaus → Sisäinen kuivaa kalvo → Sisäinen syövytys → Sisäinen AOI → Multi-Bond → Kerrospino ylös Painamalla → Poraus → PTH → Paneeli Plating → Ulkoinen kuiva kalvo → Kuviopinnoitus → Ulkoinen etsaus → Outer AOI → Solder Mask → Komponenttikappale → Pinta-ala→ Reititys → E / T → Visuaalinen tarkastus.