

PCB specification:
 PCB specification

Material	FR-4 (Standard) or FR-4 (High Tg)	Thickness	0.50Z-50Z
Thickness	0.2mm	Drill Hole	0.2mm
Surface Treatment	OSP or HASL	Plating Thickness	0.1-5mm
Surface Finish	OSP or HASL	Material	Standard PCB
Standard	ISO9001, UL, SGS	Q / Control	10PCS-100PCS
Weight	0.01kg -5kg	Quantity	10
PCBA	PCBA	Thickness	0.2mm
Price		Price	\$ 0.1- \$ 10
design		Design	0.01m3-10m3

PCB specification & PCB specification

PCB specification	16 PCB specification PCB specification oem PCB specification
PCB specification	7-12days

PCB specification

PCB specification

PCB specification

16 PCB specification PCB specification PCB specification PCB specification

Item	2014		2015 ~ 2016		2017 ~ 2018	
	Value	Value	Value	Value	Value	Value
Thickness	32	42	38	44	42	48
Thickness / Thickness (µm)	50/50	40/45	40/45	40/40	35/40	35/35
Thickness (µm)	0.15	0.10	0.15	0.10	0.15	0.10
PTH	14: 1	16: 1	16: 1	18: 1	18: 1	20: 1
N + C + N	4 + C + 4	5 + C + 5	5 + C + 5	6 + C + 6	5 + C + 5	6 + C + 6
Thickness	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6
Thickness (µm)	50	40	40	30	40	30
Thickness (µm)	75	65	65	50	50	40
Material	FR4 Megtron Nelco Rogers Heavy Copper etc.					
Thickness	Value	-	Value	-	Value	-
Thickness	HASL ENIG OSP or HASL					

