

COPPER PLATE HOLES MINIMUM .025 AVG .020 MIN .. HOLES MAY NOT NOT PLUGGED

PCB

- ENIG 4 : Tolerance: Tol: +/- 70 Ohm .

25

PCB

Lyr	Image	Foil	Flame
COMP		0.5oz	Foil 1/2oz
L2			R-5670(G) 3313 RC54%
L3		0.5oz	R-5775(G) 0.150mm H/H 37"*49"(1080*2)(RTF)
			R-5670(G) 1078 RC68%
			R-5670(G) 1035 RC70%
L4		0.5oz	R-5775(G) 0.150mm H/H 37"*49"(1080*2)(RTF)
L5		0.5oz	R-5670(G) 1078 RC68%
			R-5670(G) 1035 RC70%
L6		0.5oz	R-5775(G) 0.150mm H/H 37"*49"(1080*2)(RTF)
L7		0.5oz	R-5670(G) 1078 RC68%
			R-5670(G) 1035 RC70%
L8		0.5oz	R-5775(G) 0.140mm H/2 37"*49"(1078*2)(RTF)
L9		2oz	R-5670(G) 2116 RC54%
			R-5670(G) 2116 RC54%
			R-5670(G) 2116 RC54%
L10		2oz	R-5775(G) 0.140mm H/2 37"*49"(1078*2)(RTF)
L11		0.5oz	R-5670(G) 1035 RC70%
			R-5670(G) 1078 RC68%
L12		0.5oz	R-5775(G) 0.150mm H/H 37"*49"(1080*2)(RTF)
L13		0.5oz	R-5670(G) 1035 RC70%
			R-5670(G) 1078 RC68%
L14		0.5oz	R-5775(G) 0.150mm H/H 37"*49"(1080*2)(RTF)
L15		0.5oz	R-5670(G) 1035 RC70%
			R-5670(G) 1078 RC68%
L16		0.5oz	R-5775(G) 0.150mm H/H 37"*49"(1080*2)(RTF)
L17		0.5oz	R-5670(G) 3313 RC54%
SOLD		0.5oz	Foil 1/2oz

O-LEADING
To Be Reliable, To Be Valuable



www.o-leading.com

O-LEADING
To Be Reliable, To Be Valuable



www.o-leading.com



www.o-leading.com

