[illegible] O-[illegible]

[illegible] O-Leading [illegible] EMS [illegible] (PCBA). [illegible]
([illegible]) [illegible]
[illegible] O-[illegible] PCB [illegible] PCBA [illegible]
[illegible]:[illegible]

[illegible]

[illegible]:	[illegible]
[illegible]:	O- [illegible]
[illegible]:	FR-4 [illegible]
[illegible]:	0.1-5 [illegible]
[illegible]:	0.2 [illegible]
[illegible]:	0.2 [illegible]
[illegible]:	0.1 [illegible] 10 - [illegible]
[illegible]:	0.2 [illegible]
[illegible]:	0.01 3 [illegible] 10-3 [illegible]
[illegible]:	0.5 [illegible] 5 - [illegible]
[illegible]:	10 [illegible]
[illegible]:	[illegible]
[illegible]:	[illegible]
[illegible]:	[illegible]
[illegible]:	[illegible] OSP [illegible] HASL [illegible]
[illegible]:	[illegible]
[illegible]:	[illegible]
[illegible]:	ISO9001 [illegible] UL [illegible] RoHS [illegible] SGS0.01m3-10m3
[illegible] / CTN:	10 [illegible] 100- [illegible]
[illegible]:	0.01 [illegible] 5- [illegible]

[illegible]

[illegible]



[illegible]





[illegible]

Quick Turn Lead Time		
Layer Count:	Lead Tim	Special Requirement
1L/2L	2-3days	24 Hours,48 Hours
4L	3-4days	48 Hours
6L	4-5days	72 Hours
8L	5-6days	NA
10L	6-7days	NA
12L	7-8days	NA
14L	8-9days	NA

Standard Lead Time		
Layer Count:	Sample Lead Time	Volume order lead time
2L	4 days	10 days
4L	5 days	11 days
6L	6 days	12 days
8L	8 days	14 days
10L	10 days	16 days
12L	12 days	18 days
14L	14 days	20 days
16-32L	18 days	24 days

[illegible]

قدرات إنتاج ثنائي الفينيل متعدد الكلور

عدد الطبقات: 1 طبقة - 32 طبقة
سمك النحاس النهائي: 1 / 3 oz-12oz
عرض الخط الأدنى / التباعد الداخلي: 3.0 ميل / 3.0 ميل
الحد الأدنى لعرض الخط / التباعد الخارجي: 4.0 mil / 4.0mil
نسبة العرض إلى الارتفاع القصوى: 10: 1
سمك اللوح: 0.2 مم - 5.0 مم
الحد الأقصى لحجم اللوحة (بالبوصة): 635 * 1500 مم
الحد الأدنى لحجم الثقب: 4 مل
Plated Hole Tolerance: +/- 3mil
Blind / Buried Vias (أنواع All): نعم
عبر التعبئة (موصلة ، غير موصلة): نعم
المادة الأساسية: FR-4 ، FR-4high Tg. مادة خالية من الهالوجين ، Rogers ، ، بوليميد ، قاعدة الألومنيوم
نحاس ثقيل
التشطيبات السطحية: HASL، OSP، ENIG، HAL-LF، Immersion silver، القصدير Immersion ، حبر الكربون ، أصابع الذهب

قدرات إنتاج SMT

مادة ثنائي الفينيل متعدد الكلور: FR-4 ، CEM-1 ، CEM-3 ، لوح من الألومنيوم
الحد الأقصى لحجم ثنائي الفينيل متعدد الكلور: 510 x460mm
الحد الأدنى لحجم ثنائي الفينيل متعدد الكلور: 50 × 50 مم
سمك ثنائي الفينيل متعدد الكلور: 0.5 مم - 4.5 مم
سماكة اللوح: 0.5-4 mm
الحد الأدنى لحجم المكونات: 0201
مكون حجم الشريحة القياسي: 0603 وأكبر
ارتفاع المكون: 15 ملم
الحد الأدنى لملعب الرصاص: 0.3 مم
الحد الأدنى لملعب الكرة بغا: 0.4 مم
دقة التنسيب: +/- 0.03 مم