

PCB Specifications

PCB Specifications

Material	FR-4 (Standard)	Thickness	0.5oz-5oz.
Thickness	0.2mm	Drill Hole	0.2mm
Surface Treatment	OSP / HASL	Lead Thickness	0.1-5mm.
Process	Standard PCB	Quantity	10PCS-100PCS.
Standards	ISO9001, UL, SGS	Weight	0.01kg -5
Lead Time	7-12days.	Price	\$ 0.1- \$ 10
Volume	0.01m3-10m3.		

PCB Specifications

Material	16 Standard OEM PCB
Lead Time	7-12days.

PCB Specifications

16 Standard OEM

Item	2014.		2015 ~ 2016.		2017 ~ 2018.	
	Value 1	Value 2	Value 1	Value 2	Value 1	Value 2
Material	32.	42.	38.	44.	42.	48.
Thickness (mm)	50/50.	40/45.	40/45.	40/40.	35/40.	35/35.
Lead Thickness (mm)	0.15.	0.10.	0.15.	0.10.	0.15.	0.10.
Drill Hole (mm)	14: 1.	16: 1.	16: 1.	18: 1.	18: 1.	20: 1.
Process	n + c + n	4 + C + 4	5 + C + 5	5 + C + 5	6 + C + 6	5 + C + 5
Surface Treatment	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6
Quantity	50.	40.	40.	30.	40.	30.
Price	75.	65.	65.	50.	50.	40.
Volume						

□□□□	FR4 □□□ □□□□□□□ □□□□□□ □□□□□□ □□□□□□□□□□.					
□□□□ □□□□ PCB.	□□□	-	□□□	-	□□□	-
□□□□□ □□□□□	hasl □□□□□□ □□ □□□□□□ enig □ osp □□□□□□ □□□□□□□□ □□□□□ □□□ □□□□□□□□□□ □□□□□ □□□□□ □□□□ □□□□□□□ □□□□□ □□□□□ □□□□□ □□□□□ □□□□□□□□ □□□ □□□□□□□ □□□□□□ □□□□□					



