

Descripción del producto

8 " reconocimiento facial y quiosco de medición de temperatura

Modelo: KMT-0080U-3CAW

8 " reconocimiento facial y quiosco de medición de temperatura Información regular	
Humedad de trabajo	0 - 90% de humedad relativa, sin condensación
Spray de sal	Nivel Rp6 o superior
Propiedad antiestática	Contacto \pm 6KV, aire \pm 8KV
Poder	DC12V / 2A, 20W (MAX)
Apertura de la columna	36mm
Tamaño del equipo	252 (L) * 136 (W) * 26 (T) mm
Tamaño de pantalla	Pantalla IPS HD de 8 pulgadas
Peso	1,7 kg
Modos de embalaje	Embalado en tres cajas de cartón
Lugar de origen	China

Imágenes detalladas:

[Temperatura de alarma de fiebre no táctil](#)

8" Facial Recognition and Temperature Measurement Kiosk



IP 65 waterproof
& dustproof




Infrared temperature
measurement



Alarming
system



Linux
Operating system



Accurate face
recognition



Large-capacity
face database

Contactless Infrared temperature detection



Temperature tolerance: $\pm 0.3^{\circ}\text{C}$

Temperature measurement range: $16^{\circ}\text{C} - 40^{\circ}\text{C}$


Detection distance: $\leq 30\text{cm}$

Rapid face Recognition: less than 1s

8-inch IPS full-view high-definition display, no image smearing, no delay.

Automatic gain, automatic white balance, make the true color of the image naturally restore.

Built-in black level sensor for video surveillance, low-light recognition is more accurate.







1s

**large storage capacity to meet places
with large traffic.**

24,000 face database

Support 24000+ face comparison data and 160,000 recognition records.





Alarm system for temperature measurement and entry management



Normal temperature: pass

abnormal temperature: can't pass



- Stranger
- Temperature measurement
- No entry



Infrared temperature detection module

Binocular wide dynamic camera



Speaker

60cm/100cm pillar for your option.

2USB

Flexible installation

Desktop



turnstile



wall mounted



Tripod



Pillar



Application

Bus, supermarket, school, government, hospital, factory



customized multiple interfaces



Imágenes detalladas

















Model	KMT-0080U-3CAW
Hardware	
Processor	Dual Core Processor+ 1G memory + 16G flash
Operating system	Linux Operating system
Storage	Support TF card storage
Viewing angle	Vertical viewing angle: 30°; Horizontal viewing angle: 30°
Sensor	1/2.8" Progressive Scan CMOS(IMX307)
Lens	6mm
Communication	Support 4G \ WIFI \ bluetooth ; can be customized
Speaker	voice playback content can be customized
Temperature measurement performance	Please find the notes on last page
Measurement range	16℃ - 40℃ (Indoor without wind)
Temperature measurement	European original lens
Sensors type	Medical grade European imported sensors
Measurement accuracy	±0.3℃
Temperature resolution	0.1℃
Temperature detection distance	≤30cm
Measurement response time	300ms
Performance	
Recognition	1.2~2.2 meters, angle adjustable
Recognition distance	0.3~1.5 meters, depends on lens
Recognition time	<0.5s
Storage capacity	160,000 capture records
Face capacity	24000pcs
Screen brightness	≥400 cd/m2
Interface	
Switching output	1 way switch output, other GPIO port can be customized
Network interface	1 RJ45 10M / 100M adaptive Ethernet port, Gigabit Ethernet port can be customized
Wiegand interface	1 Wiegand interface input/output
Communication interface	1 RS485 interface
USB interface	1 USB interface
Camera	
Camera	Dual cameras, visible and near infrared, support live detection
Effective pixels	2MP, 1920*1080
Min Illumination	Color 0.01Lux @F1.2(ICR);B/W 0.001Lux @F1.2 (ICR)
SNR	≥50db(AGC OFF)
WDR	120db, ISP algorithm face partial exposure
Function	
Web side configuration	support
remote upgrade	support
LAN/ WAN	support
Regular	
Working humidity	0~90% relative humidity, no condensation
Salt spray	level Rp6 or above
Antistatic	contact ±6KV, air ±8KV
Power	DC12V/2A , 20W(MAX)
Column aperture	36mm
Equipment size	252(L) * 136 (W) * 26 (T) mm
Screen size	8 inches IPS HD screen
Weight	1.7 kg

Embalaje y envío

Empaquetado y entrega

Unidades de venta	Objeto unico			
Tamaño de paquete individual	25.3X14.5X14.5 cm			
Peso bruto individual	1.500 kg			
Tipo de paquete				
caja para exhibir	430 * 170 * 115 mm, peso: 2.1 kg.			
cartón para exhibición	500 * 195 * 425 mm, 3 piezas por caja, G.W: 8.8 kg.			
Caja de cartón del soporte	305 * 51 * 290 mm, G.W: 0.3 kg.			
Tamaño del cartón para soporte	327 * 340 * 317 mm, 6 piezas por caja, G.W: 18 kg.			
Tamaño de caja de soporte de 0.6 m	630 * 132 * 124 mm, G.W: 0.3 kg.			
0,6 m de tamaño de caja de cartón	650 * 280 * 260 mm, 4 piezas por caja, G.W: 15 kg.			
Tamaño de soporte de 1,1 m	1130 * 132 * 124 mm, G.W: 0.5 kg.			
Tamaño del cartón del soporte de 1,1 m	650 * 280 * 260 mm, 4 piezas por caja, G.W: 19.8 kg.			
Tiempo de espera				
Cantidad (piezas)	1-100	101-500	501-1000	> 1000
Est. Tiempo (días)	3	5 5	7 7	Ser negociado

Preguntas más frecuentes

Q: ¿Qué puedo obtener el precio?

R: Por lo general, cotizamos dentro de las 24 horas posteriores a la recepción de su consulta. Si es muy urgente para obtener el precio, díganos en su correo electrónico para que consideremos su consulta como una prioridad.

P: ¿Cuál es su plazo comercial de entrega?

A: aceptamos puerto de destino EXW, FOB Shenzhen o CIF. Puedes elegir el que es el más conveniente o rentable para usted.

P: ¿Qué pasa con el tiempo de entrega para la producción en masa?

R: Honestamente, depende de la cantidad de la orden y la temporada en que realiza la orden. El pedido de muestra es dentro de 2 días. El pedido de OEM / OEM necesitará tiempo extra.