

Tervetuloa O-Leadingiin

O-Leading pyrkii olemaan yhden luukun kumppanisi EMS-toimitusketjussa, mukaan lukien piirilevysuunnittelu, piirilevyjen valmistus ja piirilevykokoonpano (PCBA). Tarjoamme joitain edistyneimpiä piirilevytekniikoita, mukaan lukien HDI-piirilevyt, monikerroksiset piirilevyt, jäykät ja joustavat piirilevyt. Voimme tukea nopeasta käännöksestä prototyypistä keski- ja massatuotantoon.

Yleisesti ottaen maailmanlaajuiset asiakkaamme ovat erittäin vaikuttuneita palveluistamme: nopea reagointi, kilpailukykyinen hinta ja sitoutuminen laatuun. Arvokkaamman teknisen palvelun ja kokonaisratkaisun tarjoaminen on tapa, jolla O johtaa eteenpäin.

Tulevaisuuden näkökulmasta O-Leading keskittyy elektroniikan valmistusteknologian innovaatioihin ja kehitykseen kuten aina, ja ponnistelee jatkuvasti PCB: n ja PCBA: n yhden luukun palvelun tarjoamiseksi ensiluokkaisia palveluja ja lisäarvoa asiakkaillemme.

LISÄÄ TIETOJA KLIKKAAMALLA NÄITÄ [Cräätälöinti HDI-piirilevyjen piirilevyjen valmistaja](#)

WE ALWAYS PROVIDE YOU
BEST RIGID-FLEXIBLE CIRCUIT

O-LEADING
To Be Reliable, To Be Valuable

WE ALWAYS PROVIDE YOU
BEST HIGH DENSITY INTERCONNECT PCB



Keep **LEARNING**

There's a phrase in Buddhism, 'Beginner's mind.'


It's wonderful to have a beginner's mind

WE HAVE A **DREAM**

Keep **RUNNING**

I would like to live to study and not study to live.

---Bacon




Tuotteen Kuvaus

Kiina High TG PCB -toimittaja kuuma myynti 8L monikerroksinen HDI korkea Tg 180 pcb 3/3 mil BGA -suunnittelulla ja 30u "kovakullatulla pinnoitteella teolliseen ohjauspaneeliin

TOP QUALITY PCB

O-LEADING
To Be Reliable, To Be Valuable



MAKE YOUR IDEA COME **TRUE**

TOP QUALITY PCB


0-LEADING
To Be Reliable, To Be Valuable



MAKE YOUR IDEA COME **TRUE**


TOP QUALITY PCB

O-LEADING
To Be Reliable, To Be Valuable



MAKE YOUR IDEA COME **TRUE**


O-LEADING
To Be **Reliable**, To Be **Valuable**



MAKE YOUR IDEA COME TRUE

TOP QUALITY PCB


O-LEADING
To Be Reliable, To Be Valuable



MAKE YOUR IDEA COME **TRUE**

TOP QUALITY PCB

O-LEADING
To Be Reliable, To Be Valuable



MAKE YOUR IDEA COME **TRUE**

TOP QUALITY PCB

O-LEADING
To Be Reliable, To Be Valuable



MAKE YOUR IDEA COME **TRUE**

Market Share

CONSUMER ELECTRONICS

AUTOMOTIVE ELECTRONICS

INDUSTRIAL CONTROL

INTELLECTUALIZED HOUSEHOLD CONTROL

OTHER



30%
CONSUMER ELECTRONICS




18%
INTELLECTUALIZED HOUSEHOLD CONTROL

20%
AUTOMOTIVE ELECTRONICS




12%
OTHER

20%
INDUSTRIAL CONTROL




Product types



■ FR-4 PCB ■ MC PCB ■ rigid-flexible PCB

Product layers

■ 1L ■ 2L ■ 4L ■ 6L ■ >8L



Production Process

18 years experience in one-stop PCB and PCBA, we can make your idea come true,



Tiimimme



Factory PCB



Automatic vacuum press machine



Drilling Machine



Pattern Plating Machine



Scrubbing Machine



Developing Machine



Routing Machine



High-speed flying probe machine



E-test Machine

Factory SMT



To be *RELIABLE*

Quality first ,
Customer supreme ,
Scientifically management ,
Striving for famous brand



THE CUSTOMER IS KING



To be *VALUABLE*

Science and technology keeps head ,
Put people first ,
Be precise and practical ,
contribute sincerely

Skyworth 创维

HAT 和而泰
HAT INTELLIGENT CONTROL

dongweikeji
东威科技

美的 Midea

STAR-NET
星网锐捷

FORYOU
ADAYO 华阳集团

EDIFIER®

Cultraview 金锐显

3nod 三诺

T&W

TCL

AcBel 康舒科技
ACBEL POLYTECH INC.

Honeywell

Schneider
Electric

ZTE 中兴

EMERSON

BYD

PHILIPS

TE
connectivity

VIDEOTON

O-LEADING CUSTOMER REVIEW

CUSTOMER VOICE IS **EXTREMELY IMPORTANT** TO US

订单编号: 49335463501024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



High quality usb power pcb ,pcba manufacturer

★★★★★

Fancy has done an excellent job, whenever we write, she answered us within 1 second, O-leading is very perfect with fast delivery, fast logistics, the most important thing is good quality, good packaging, thank you!

[回复该评论](#)



oem customized rohs pcb drawing schematic s...

★★★★★

We received the boards, the quality is very good, the price is very reasonable, Fancy is very nice & smart & experienced, the logistics is super fast, I will come to see more in the future.

[回复该评论](#)

订单编号: 49024962001024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



High TG180 FR-4 Circuit HDI PCB 94V0 Board ...

★★★★★

perfect product, perfect PCB supplier!

[回复该评论](#)



oem customized rohs pcb drawing schematic s...

★★★★★

Very good and professional PCB product as usual!

[回复该评论](#)



Strip LED Aluminum FR-4 lighting PCB board 9...

★★★★★

High quality, fast delivery, good service, competitive price, lucky and happy to purchase from O-leading!

[回复该评论](#)

订单编号: 40938623501024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



High TG180 FR-4 Circuit HDI PCB 94V0 Board ...

★★★★★

This is a very difficult PCB design, but we are lucky to find O-leading to support the PCB for us very good to a PCB supplier.



universal FR4 Multilayer PCB washing machine...

★★★★★

Fancy gives us very excellent service, very professional and experienced, O-leading is the best one of our suppliers, very happy to work with them.

订单编号: 40938623501024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



High quality Keyboard pcb & pcba Factory SMT...

★★★★★

Top quality, it's the right choice to choose O-leading to make the PCB & PCBA

[回复该评论](#)

订单编号: 40938623501024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



Professional Printed Circuit Board Manufacturer...

★★★★★

Very high quality PCB products, O-leading is the best PCB supplier that we have ever worked with.

订单编号: 44068794501024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



High TG180 FR-4 Circuit HDI PCB 94V0 Board ...

★★★★★

We bought two batches, one by DHL, the other one by air, good quality and fast delivery!

LISTEN TO CUSTOMER VOICE

订单编号: 4090347501024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



Strip LED Aluminum FR-4 lighting PCB board 9...

★★★★★

Very fast delivery! Fantastic, good job!!



Professional Printed Circuit Board Manufacturer...

★★★★★

Very happy to great support from O-leading, they are not only professional on the PCB, but also provide good PCB products, very good supplier!

订单编号: 36919647001024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



AML-S802 Quad-core Android embedded board...

★★★★★

Good products



Fast delivery low cost pcb fabrication O-leadin...

★★★★★

Good supplier

订单编号: 37378603001024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



hot sale rigid-flexible PCB with 0.2mm BGA an...

★★★★★

very professional supplier



High Quality custom FPCB/Flex PCB/FPC/Flexi...

★★★★★

Good product



OEM ODM PCBA Bluetooth Wireless Marking G...

★★★★★

high soldering quality



Electronic parts haptic pcba Circuit Board asse...

★★★★★

Very Good product

订单编号: 36919647001024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



Lidar IR Sensor board pcba(H08R6x)

★★★★★

perfect product



Customized PCBA design PCB design

★★★★★

perfect



Audio Speaker and Headphone Jack (H07R3x)

★★★★★

High quality, good

订单编号: 37378603001024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



half hole pcb, half hole pcb module, half hole m...

★★★★★

Top half hole pcb supplier, very perfect goods



High Quality custom FPCB/Flex PCB/FPC/Flexi...

★★★★★

this rigid-flexible pcb quality is perfect!



Electronic parts haptic pcba Circuit Board asse...

★★★★★

Very satisfied with O-leading products and quality, especially their on-time delivery, fantastic!

订单编号: 37378603001024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)



Raspberry pi 0 Zero Raspberry Pi Zero Pi W ver...

★★★★★

Fantastic products!!



double layer pcb with red S/M and LF-HASL su...

★★★★★

Good!

Be **kind** to your client,
because he has many choices,
but he chooses you instead.

Sertifikaatit





No. SZXEC1900530401

Date: 30 Mar 2019

Page 1 of 6

O-LEADING SUPPLY CHAIN (HK) CO., LIMITED

1313, FLOOR 13, FORTUNE BUILDING, DANSHUI TOWN, HUIYANG DISTRICT, HUIZHOU, GUANGDONG, CHINA

The following sample(s) was/were submitted and identified on behalf of the clients as : OSP

SGS Job No. : RP19-005089 - SZ

Date of Sample Received : 22 Mar 2019

Testing Period : 22 Mar 2019 - 30 Mar 2019

Test Requested : Selected test(s) as requested by client.

Test Method : Please refer to next page(s).

Test Results : Please refer to next page(s).

Conclusion : Based on the performed tests on submitted sample(s), the results of Lead, Mercury, Cadmium, Hexavalent chromium, Polybrominated biphenyls (PBBs), Polybrominated diphenyl ethers (PDBEs) and Phthalates such as Bis(2-ethylhexyl) phthalate (DEHP), Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP), and Diisobutyl phthalate (DIBP) comply with the limits as set by RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU.

Signed for and on behalf of
SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Tina Fan
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed on the back, available on request or accessible at <http://www.spa.com/terms-and-conditions> and, for electronic formal documents, subject to Terms and Conditions for Electronic Documents at <http://www.spa.com/terms-and-conditions/terms-e-document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is deemed to have read, understood and accepted the terms and conditions of the document and to have agreed to follow the Client's instructions, if any. The Company's sole responsibility is to its Client and the document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without the prior written permission of the Company. Any unauthorized use or reproduction of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the samples tested.

SGS S&P, No.4, Jiangnan Road, Baotou, Langfang District, Shanxi, China. 518129 t (86-756) 25326888 f (86-756) 83106190 www.sgsgroup.com.cn
中国·深圳·龙岗区坪地街道430号江鹏工业园4楼SGS总部 邮编 518190 t (86-756) 25326888 f (86-756) 83106190 e sgs.china@sgs.com

Member of the SGS Group (SGS SA)



No. SZXEC1900530401

Date: 30 Mar 2019

Page 2 of 6

Test Results :

Test Part Description:

Specimen No.	SGS Sample ID	Description
SN1	SZX19-005304.001	Green™PCB

Remarks :

(1) $1 \text{ mg/kg} = 1 \text{ ppm} = 0.0001\%$

(2) MDL = Method Detection Limit

(3) ND = Not Detected (< MDL)

(4) "-" = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method : With reference to IEC 62321-4:2013+A1:2017, IEC62321-5:2013, IEC62321-7-2:2017, IEC 62321-6:2015 and IEC62321-8:2017, analyzed by ICP-OES, UV-Vis and GC-MS.

Test Item(s)	Limit	Unit	MDL	Q27
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	8
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (Cr(VI))	1,000	mg/kg	8	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tri bromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND
Dibromodiphenyl ether	-	mg/kg	5	ND
Tri bromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND

[illegible]

SGS B.V., Leiden, The Netherlands
SGS B.V., CN, Dongchuan Industrial Park, No.430, Jiuji Road, Baidian, Longgang District, Shenzhen, China 518129
中国·深圳·龙岗区田田路430号江田工业园4楼SGS大厦 邮编: 518129

Member of the SGS Group (SGS SA)



ZPMV2.E490354 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

O-LEADING SUPPLY CHAIN (HK) CO LTD

E490354

ROOM 1205, 12/F
TAI SANG BANK BLDG
130-132 DES VOEUS ROAD
CENTRAL, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Max						
	Min	Min			Area	Solder	Oper	Flame	Meets	C		
	mm(in)	mm(in)			Diam	Limits	Temp	Class	UL796	T		
Multilayer (mass laminate) printed wiring boards.												
O-LEADING-401	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	130	V-0	-	-	
O-LEADING-407	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.7 (0.4)	260	10	130	V-0	All	-	
Multilayer printed wiring boards.												
O-LEADING-408	0.125 (0.005)	0.125 (0.005)	12 (0.47) Int:136	DS	50.8 (2.0)	280	20	130	V-0	All	*	
Single layer printed wiring boards.												
O-LEADING-002	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	All	-	
O-LEADING-003	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	130	V-0	▲	-	
O-LEADING-033	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	All	-	
O-LEADING-205	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.6 (2.7)	260	10	130	V-0	All	-	
O-LEADING-206	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	All	-	
O-LEADING-D01	0.14 (0.006)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	All	*	
O-LEADING-S01	0.25 (0.010)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	260	4	130	V-0	All	*	

WIRING, PRINTED - COMPONENT | UL Product iQ

O-LEADING-S02	0.2 (0.008)	0.2 (0.008)	17 (0.67)	SS	25.4 (1.0)	260	4	130	HB	▲
O-LEADING-S03	0.25 (0.010)	0.25 (0.010)	34 (1.34)	SS	25.4 (1.0)	260	4	130	V-0	All

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2019 UL LLC”

Prosessikapasiteetti

Piirilevyjen tuotantokapasiteetti

Kerroslaskenta	1 kerros-32 kerros
Valmiit kuparipaksuudet	1 / 3oz-12oz
Min. Viivan leveys / sisäinen etäisyys	3,0mil / 3,0mil
Pienin viivan leveys / ulkoinen etäisyys	4,0mil / 4,0mil
Suurin kuvasuhde	10: 1
Levyn paksuus	0,2 - 5,0 mm
Paneelin enimmäiskoko (tuumaa)	635 * 1500mm
Porattu reikien vähimmäiskoko	4mil
Kiinnitetty reiän suvaitsevaisuus	+/- 3mil
Blind / Buried Vias (AII-tyypit)	JOO
Täytön kautta (johtava, ei-johtava)	JOO
Pohjamateriaalia	FR-4, FR-4korkea Tg halogeeniton materiaali, Rogers, alumiinipohja, Polyimidi, raskas kupari
Pintakäsittely	HASL, OSP, ENIG, HAL-LF, Immersion hopea, Immersion Tin, kultaiset sormet, hiilimustetta

SMT-tuotantokapasiteetti

PCB-materiaali	FR-4, CEM-1, CEM-3, alumiinilevy
Max PCB-koko	510x1500mm
Pienin piirilevykoko	50x50mm
Piirilevyn paksuus	0,5 - 4,5 mm
Levyn paksuus	0,5-4 mm
Komponenttien vähimmäiskoko	0201
Normaali sirukokoinen komponentti	0603 tai suurempi
Komponentin enimmäiskorkeus	15mm
Pienin lyijyn nousu	0,3 mm
Min BGA-pallon piki	0,4 mm
Sijoittamisen tarkkuus	+/- 0,03 mm

Pakkaus ja toimitus

Shipping service



Quick Turn Lead Time		
Layer Count:	Lead Tim	Special Requirement
1L/2L	2-3days	24 Hours,48 Hours
4L	3-4days	48 Hours
6L	4-5days	72 Hours
8L	5-6days	NA
10L	6-7days	NA
12L	7-8days	NA
14L	8-9days	NA

Standard Lead Time		
Layer Count:	Sample Lead Time	Volume order lead time
2L	4 days	10 days
4L	5 days	11 days
6L	6 days	12 days
8L	8 days	14 days
10L	10 days	16 days
12L	12 days	18 days
14L	14 days	20 days
16-32L	18 days	24 days

UKK

1. [Piirilevyjen toimittaja](#) Kuinka O-Leading varmistaa laadun? Korkea laatutaso saavutetaan seuraavilla tavoilla.

- 1.1 Prosessia valvotaan tiukasti ISO 9001: 2008 -standardien mukaisesti.
- 1.2 Ohjelmistojen laaja käyttö tuotantoprosessin hallinnassa
- 1.3 Huipputason testauslaitteet ja työkalut. Esimerkiksi. Flying Probe, röntgentarkastus, AOI (automatisoitu optinen tarkastaja) ja ICT (piirin sisäinen testaus).
- 1.4 Eriytynyt laadunvarmistusryhmä vikatapausten analysointiprosessilla
- 1.5 Henkilöstön jatkuva koulutus

2. Kuinka O-Leading pitää hintasi kilpailukykyisenä?

Viime vuosikymmenen aikana monien raaka-aineiden (esim. Kupari, kemikaalit) hinnat ovat kaksinkertaistuneet, kolminkertaistuneet tai nelinkertaistuneet; Kiinan valuutan RMB oli noussut 31% Yhdysvaltain dollariin nähden; Myös työvoimakustannuksemme nousivat merkittävästi.

O-Leading on kuitenkin pitänyt hintamme vakaana. Tämä omistaa kokonaan innovaatiomme kustannusten vähentämisessä, jätteen välttämässä ja tehokkuuden parantamisessa. Hintamme ovat erittäin kilpailukykyisiä teollisuudessa samalla laatutasolla.

Uskomme win-win-kumppanuuteen asiakkaidemme kanssa. Kumppanuudestamme on molemminpuolista

hyötyä, jos voimme tarjota sinulle edelleen-kustannukset ja -laadun.

3. Millaisia levyjä O-Leading voi käsitellä?

Tavalliset FR4-, korkea-TG- ja halogeenittomat levyt, Rogers, Arlon, Telfon, alumiini / kupari-pohjaiset levyt, PI jne.

4. Mitä tietoja tarvitaan PCB- ja PCBA-tuotantoon?

4.1 BOM (Bill of Materials) viitetunnisteilla: osan kuvaus, valmistajan nimi ja osanumero.

4.2 Piirilevyn Gerber-tiedostot.

4.3 Piirilevyn valmistuspiirustus ja PCBA-kokoonpanopiirustus.

4.4 Testimenettelyt.

4.5 Mahdolliset mekaaniset rajoitukset, kuten kokoonpanon korkeusvaatimukset.

5. Mikä on tyypillinen prosessivirta monikerroksiselle piirilevylle?

Materiaalin leikkaus → Sisempi kuiva kalvo → sisäinen syövytys → Sisempi AOI → Monisidos → Kerrospino
ylös Puristaminen → Poraus → PTH → Paneelipinnoitus → Ulkokuiva kalvo → Kuvion päällystys → Ulkoinen
syövytys → Ulkoinen AOI → Juotosmaski → Komponenttimerkki → Pintakäsittely → Reititys → E / T →
Silmämääräinen tarkastus.

6. Mitkä ovat HDI-valmistuksen tärkeimmät laitteet?

Tärkeimpien laitteiden luettelo on seuraava: Laserporakone, puristuskone, VCP-linja, automaattinen
valotuskone, LDI ja niin edelleen. Meillä olevat laitteet ovat alan parhaita, laserporakoneet ovat Mitsubishi
ja Hitachi, LDI-koneet ovat Screen (Japani), Automaattiset valotuskoneet ovat myös Hitachilta, jotka kaikki
tekevät meistä vastaamaan asiakkaan teknisiin vaatimuksiin.

7. Kuinka monta pintakäsittelyä O-lyijy voi tehdä?

O-johtajalla on täysi sarja pintakäsittelyjä, kuten: ENIG, OSP, LF-HASL, kulloitus (pehmeä / kova),
upotettava hopea, tina, hopeapinnoitus, upotettava tina pinnoitus, hiilimuste ja niin edelleen. HDI: ssä
yleisesti käytetty OSP, ENIG, OSP + ENIG, suosittelemme yleensä asiakkaan tai OSP OSP + ENIG: n
käyttöä, jos BGA PAD -koko on alle 0,3 mm.

8. Mikä on kyky FPC: lle? Voiko O-Leading tarjota myös SMT-palvelua?

O-Leading voi valmistaa FPC: n yksikerroksisesta 8-kerrokseen, työpaneelin koko voi olla jopa 2000 mm *
240 mm, katso yksityiskohdat sivulta "Flex Capability". Tarjoamme myös SMT yhden luukun palvelua
asiakkaalle. ([PCBA-valmistaja](#))

9. Mitkä ovat tärkeimmät tekijät, jotka vaikuttavat piirilevyn hintaan?

Materiaali;
Pinnan viimeistely;
Teknologian vaikeus;
Erilaiset laatukriteerit;
PCB-ominaisuudet;
Maksuehdot;
Eri valmistusmaat.

10. Mikä on PCB: n, PWB: n ja FPC: n määritelmä ja mikä on ero?

Piirilevy on lyhenne sanoista piirilevy;

PWB on lyhenne sanoista Printed Wire Board, mikä tarkoittaa samaa kuin piirilevy;

FPC on lyhenne sanoista Flexible Printed Board.

11. Mitkä tekijät tulisi ottaa huomioon valittaessa materiaalia piirilevylle?

Seuraavat tekijät on otettava huomioon, kun valitsemme materiaalia PCB: lle:

Materiaalin Tg-arvon tulisi olla suurempi kuin käyttölämpötila;

Matalalla CTE-materiaalilla on hyvä lämpöstabiilisuus;

Hyvä lämmönkestävyys: Normaalisti PCB: n vaaditaan kestämiään 250 °C vähintään 50 sekunnin ajan.

Hyvä tasaisuus; Sähköisten ominaisuuksien huomioon ottamiseksi suuritaajuisissa piirilevyissä käytetään pienihäviöistä / suurta läpäisevyyttä sisältävää materiaalia;

Polyimidilasilasisubstraatti, jota käytetään joustavaan PCB: hen; Metalliydintä käytetään, kun tuotteella on tiukka lämpövaatimus

hajaantuminen.

12. Mitkä ovat O-Leadingin rigid-flex PCB: n edut?

O-Leadingin jäykällä joustavalla piirilevyllä on sekä FPC: n että PCB: n merkit, joten sitä voidaan käyttää joissakin erikoistuotteissa. Osa on joustava, kun taas toinen osa jäykkä, se voi auttaa säästämään tuotteen sisätilaa, vähentämään tuotteen määrää ja parantamaan suorituskykyä.

13. Kuinka impedanssi lasketaan?

Impedanssinhallintajärjestelmä tehdään käyttämällä joitain testikuponkeja, SI6000 soft ja POLAR INSTRUMENTSIN CITS 500s -laitteita. Laite mittaa impedanssin edustavalla radan kokoonpanokupongilla, jonka asiakas on antanut meille määritetyn arvon ja toleranssin.