

Tervetuloa O-johtaviin

O-johtava pyrkii olemaan yhden luukun ratkaisu kumppani EMS-toimitusketjussa, mukaan lukien PCB-suunnittelu, PCB-valmistus ja PCB-kokoonpano (PCBA). Tarjoamme joitakin kehittyneimmistä PCB-tekniikoista, mukaan lukien HDI PCB: t, monikerroksiset PCB: t, jäykät joustavat PCB: t. Voimme tukea nopeasti vuoroprototyypin keskipitkän ja massatuotantoon.

Yleensä maailmanlaajuiset asiakkaamme ovat erittäin vaikuttuneita palveluistamme: nopea vastaus, kilpailukykyinen hinta ja laatu sitoutuminen

Tulevaisuuden näköinen O-johtava keskittyy elektroniikan valmistustekniikan innovointiin ja kehittämiseen, ja tehdä pysyviä ponnisteluja PCB & PCBA: n yhden luukun palveluun tarjotakseen ensiluokkaisia palveluja ja luo enemmän arvoa asiakkaillemme. [Kaksipuolinen PCB Kiinassa](#)

Olemme ammatillinen PCB-valmistaja, jossa on yli kymmenen vuoden kokemuksia. Tuotteiden valikoimayhden, kahden puolen, monikerroksinen PCB, joustavat PCB ja MCPCB. We voivat tarjota nopean prototyypipalvelu - S / S 24 tuntia, 4-8layers vuonna 48-96 työ- tuntia tuotantoaika.

Kuparilevyn reikiä vähintään 0,025 avg, .020 min .. Reiät eivät ehkä ole kytkettynä

Pakkaus väritöntä läpinäkyvällä kuplakalvolla, 25 kpl / laukku, laita kuivausmerkille, laita kosteuden indikaattorikortti yläreunaan

Tuotteen Kuvaus

Pikatiedot

Lähtöisin	Guang Dong, Kiina (Manner)	Tuotenimi	O-johtava
Pohjamateriaalia	FR-4, alumiini	Kuparipaksuus	0.5oz-5oz
Min. Reiän koko	0,2 mm	Min. Viivan leveys	0,2 mm
Pinnan viimeistely	Upotus kulta, OSP, Lead Free Hasl	Paksuus	0,1-5mm
sovellettava	LED, matkapuhelin, ilmastointilaitteet, pesukoneet	merkki	Teollisuuden ohjaus PCB
sertifikaatit	ISO9001, UL, ROHS, SGS	Q / CTN:	10PCS-100PCS
paino	0,01 kg -5kg	MOQ:	10 kpl
väri-	Sininen, punainen, vihreä, musta. Yellow	Min. Riviväli	0,2 mm
Mallinumero	Power Bank PCB: n kokoonpano PCBA-valmistaja	hinta	\$ 0.1 - 10 dollaria
Desiule tyyppi	Asiakkaan vaatimus	koko	0,01m3-10m3


Tuotantokyky


16 vuotta ammatillinen OEM PCB-kortin valmistus

tuote	2014		2015 ~ 2016		2017 ~ 2018	
	Määrä	Näyte	Määrä	Näyte	Määrä	Näyte
Kerroslaskenta	32	42	38	44	42	48

Min Line / Space (µm)	50/50	40/45	40/45	40/40	35/40	35/35
Min porausreikä Halkaisija (mm)	0,15	0,10	0,15	0,10	0,15	0,10
Kuvasuhde pth	14: 1	16: 1	16: 1	18: 1	18: 1	20: 1
N + c + n	4 + C + 4	5 + C + 5	5 + C + 5	6 + C + 6	5 + C + 5	6 + C + 6
Kaikki kerroksen yhteenliittäminen	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6
Levyn täyttö	JOO	-	JOO	-	JOO	-
Min. Core-paksuus (sulje kupari) (µm)	50	40	40	30	40	30
Min. Laserporausalkaisija (µm)	75	65	65	50	50	40
Kautta haudattu reikä / pinottu kautta	JOO	-	JOO	-	JOO	-
Materiaali	FR4, Megtron, Nelco, Rogers, Raskas kupari jne.					
Sulautettu kondensaattori PCB	JOO	-	JOO	-	JOO	-
Pintaprosessi	Lyijytön HASL, ENIG, OSP, upotus hopea, upotus tina, Flash kulta, kulta sormi, valikoiva kova kultapinnoitus, Peelable juotosmaski, hiili muste					







www.o-leading.com

[Painettu piirilevy Ulchier](#)

Tiimimme



Factory PCB



Automatic vacuum press machine



Drilling Machine



Pattern Plating Machine



Scrubbing Machine



Developing Machine



Routing Machine



High-speed flying probe machine



E-test Machine

Factory SMT



Sertifikaatit





Test Report

No. SZXEC1900530401

Date: 30 Mar 2019

Page 1 of 6

O-LEADING SUPPLY CHAIN (HK) CO., LIMITED

1313.FLOOR 13, FORTUNE BUILDING, DANSHUI TOWN, HUIYANG DISTRICT, HUIZHOU, GUANGDONG, CHINA

The following sample(s) was/were submitted and identified on behalf of the clients as : OSP

SGS Job No. : RP19-005089 - SZ

Date of Sample Received : 22 Mar 2019

Testing Period : 22 Mar 2019 - 30 Mar 2019

Test Requested : Selected test(s) as requested by client.

Test Method : Please refer to next page(s).

Test Results : Please refer to next page(s).

Conclusion : Based on the performed tests on submitted sample(s), the results of Lead, Mercury, Cadmium, Hexavalent chromium, Polybrominated biphenyls (PBBs), Polybrominated diphenyl ethers (PBDEs) and Phthalates such as Bis(2-ethylhexyl) phthalate (DEHP), Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP), and Diisobutyl phthalate (DIBP) comply with the limits as set by RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU.

Signed for and on behalf of
SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Tina Fan
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/terms-and-conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/terms-and-conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions. If any, the Company's sole responsibility is to the Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

www.sgs.com/terms-and-conditions
SGS (UK) Ltd, Regent House, 100 Abchurch Lane, London EC4N 3DF, United Kingdom. Tel: 5181200 | Fax: 7551200888 | Email: sgs@sgs.com or sgs.china@sgs.com
中國·深圳·支那區新嘉坡牛車水430牛車水工業區4樓SGS大樓 電話: 5181200 | 傳真: 7551200888 | 郵箱: sgs@sgs.com 或 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



Test Report

No. SZXEC1900530401

Date: 30 Mar 2019

Page 2 of 6

Test Results :

Test Part Description :

Specimen No.	SGS Sample ID	Description
SN1	SZX19-005304.001	Green"PCB"

Remarks :

- (1) 1 mg/kg = 1 ppm = 0.0001%
- (2) MDL = Method Detection Limit
- (3) ND = Not Detected (< MDL)
- (4) "-" = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method : With reference to IEC 62321-4:2013+A1:2017, IEC 62321-5:2013, IEC 62321-7-2:2017, IEC 62321-6:2015 and IEC 62321-8:2017, analyzed by ICP-OES, UV-Vis and GC-MS.

Test item(s)	Limit	Unit	MDL	Q/Z
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	8
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (Cr(VI))	1,000	mg/kg	8	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tribromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND
Dibromodiphenyl ether	-	mg/kg	5	ND
Tribromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/terms-and-conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/terms-and-conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions. If any, the Company's sole responsibility is to the Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

www.sgs.com/terms-and-conditions
SGS (UK) Ltd, Regent House, 100 Abchurch Lane, London EC4N 3DF, United Kingdom. Tel: 5181200 | Fax: 7551200888 | Email: sgs@sgs.com or sgs.china@sgs.com
中國·深圳·支那區新嘉坡牛車水430牛車水工業區4樓SGS大樓 電話: 5181200 | 傳真: 7551200888 | 郵箱: sgs@sgs.com 或 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



ZPMV2.E490354 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

O-LEADING SUPPLY CHAIN (HK) CO LTD

E490354

ROOM 1205, 12/F
TAI SANG BANK BLDG
130-132 DES VOEUS ROAD
CENTRAL, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Max					
	Min	Min			Area	Solder	Oper	Meets	C		
	Edge	Thk			Diam	Limits	Temp	Flame	UL796	T	
mm(in)	mm(in)			mm(in)	C	sec	C	Class	DSR	I	
Multilayer (mass laminate) printed wiring boards.											
O-LEADING-401	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	130	V-0	-	-
O-LEADING-407	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.7 (0.4)	260	10	130	V-0	All	-
Multilayer printed wiring boards.											
O-LEADING-408	0.125 (0.005)	0.125 (0.005)	12 (0.47) Int:136	DS	50.8 (2.0)	280	20	130	V-0	All	*
Single layer printed wiring boards.											
O-LEADING-002	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	All	-
O-LEADING-003	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	130	V-0	▲	-
O-LEADING-033	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	All	-
O-LEADING-205	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.6 (2.7)	260	10	130	V-0	All	-
O-LEADING-206	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	All	-
O-LEADING-D01	0.14 (0.006)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	All	*
O-LEADING-S01	0.25 (0.010)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	260	4	130	V-0	All	*

WIRING, PRINTED - COMPONENT | UL Product iQ

O-LEADING-S02	0.2 (0.008)	0.2 (0.008)	17 (0.67)	SS	25.4 (1.0)	260	4	130	HB	▲	*
O-LEADING-S03	0.25 (0.010)	0.25 (0.010)	34 (1.34)	SS	25.4 (1.0)	260	4	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2019 UL LLC”

Shipping service



Quick Turn Lead Time		
Layer Count:	Lead Tim	Special Requirement
1L/2L	2-3days	24 Hours,48 Hours
4L	3-4days	48 Hours
6L	4-5days	72 Hours
8L	5-6days	NA
10L	6-7days	NA
12L	7-8days	NA
14L	8-9days	NA

Standard Lead Time		
Layer Count:	Sample Lead Time	Volume order lead time
2L	4 days	10 days
4L	5 days	11 days
6L	6 days	12 days
8L	8 days	14 days
10L	10 days	16 days
12L	12 days	18 days
14L	14 days	20 days
16-32L	18 days	24 days

Prosessin kyky

PCB-tuotantominaisuudet

Kerroslaskenta: 1Layer-32Layer

Valmis kupari Paksuus: 1 / 3oz-12oz

Min Line Leveys / Sijainti Sisäinen: 3.0mil / 3.0mil

Min Line Leveys / Spacing Ulkoinen: 4.0mil / 4.0mil

Max kuvasuhde: 10: 1

Hallituksen paksuus: 0,2 mm - 5.0mm

Max-paneelin koko (tuumaa): 635 * 1500mm

Pienin porausreikä Koko: 4mil

Pied Reikien toleranssi: +/- 3mil

BiD / Haudattu Vias (All-tyypit): Kyllä

Täytä (johtava, ei-johtava): Kyllä

Perusmateriaali: FR-4, FR-4HIGH TG.HALogen Free materiaali, Rogers, Aluminium Base,Polyimidi,

Raskas kupari

Pintapäälyste: HASL, OSP, ENIG, Hal-LF, LMMERSION SILVER,LMMERSION TIN, KULJETUKSET, Hiilimen muste

SMT Tuotantoominaisuudet

PCB Materiaali: FR-4, CEM-1, CEM-3, alumiinipohjainen levy

Max PCB koko: 510x460mm

Min PCB koko: 50x50mm

PCB-paksuus: 0,5 mm - 4,5 mm

Hallituksen paksuus: 0,5-4mm

MIN Komponentit Koko: 0201

Standardi sirun kokoinen komponentti: 0603 ja suurempi

Komponentti Max Korkeus: 15mm

Min Lead Pitch: 0,3mm

Min Bga Ball Pitch: 0.4mm

Sijoittelun tarkkuus: +/- 0.03mm