

# Welcome to O-leading

O-Leading strives to be your one stop solution partner in EMS supply chain, including PCB design , PCB fabrication and PCB assembly ,We provide some of the most advanced PCB technology, including HDI PCBs,multilayer PCBs, Rigid-Flexible PCBs.We can support from quick turn prototype to medium & mass Production.([Professional Rigid Flexible PCB Supplier for Raspberry Pi 4 ABS Case](#))

In general, our global customers are very impressed with our services:Rapid response, competitive price and quality commitment.Providing more valuable technical service and overall solution is the way O-leading forward.

Looking to the future, O-leading will concentrate on the innovation and development of electronics manufacturing technology as always, and make persistent efforts on PCB & PCBA one-stop service to provide first-class services and create more value for our customers.

PLEASE CLICK THESE FOR MORE INFORMATION [Low Cost PCB Fabrication POE Oem Manufacturing](#)

The banner is divided into two main sections. The top section has a dark blue background with a glowing blue globe and network lines. It features the O-LEADING logo (To Be Reliable, To Be Valuable) and the text 'WE ALWAYS PROVIDE YOU' in a white box. Below this is a white box with the text 'BEST HIGH DENSITY INTERCONNECT PCB'. To the right is a large, complex green PCB. Below the text are several smaller images of different PCB types. The bottom section has a similar background but includes images of the Moon and Jupiter. It features the text 'WE ALWAYS PROVIDE YOU' in a white box and 'BEST RIGID-FLEXIBLE CIRCUIT' in a white box. To the right is a large, complex green PCB being held by a hand.

**O-LEADING**  
To Be Reliable, To Be Valuable

WE ALWAYS PROVIDE YOU

**BEST HIGH DENSITY INTERCONNECT PCB**

WE ALWAYS PROVIDE YOU

**BEST RIGID-FLEXIBLE CIRCUIT**

## Product Description

# Raspberry Pi 4 8GB RAM

More Powerful Processor, Richer Multi-Media Capability, Faster Networking



## IMPROVEMENTS OF V1.2


1. In addition to the official USB Type-C cable, Pi 4B V1.2 now supports more other USB Type-C cables
2. Relocates the WLCSP SD card voltage switch, to protect the Pi 4B better
3. Optimizes silkscreen printing, to minimize the soldering and bridging in manufacturing process



\* The Raspberry Pi 4 is optional, up to your choice.

# Raspberry Pi 4 Completely Upgraded

More Powerful Processor, Richer Multi-Media Capability, Faster Networking



## BCM2711B0

64-bit 1.5GHz Quad-core Processor

## Choice Of RAM

2GB / 4GB / 8GB

## 4K Dual HDMI

4K High Resolution Dual Displays

## Faster Networking

Gigabit ETH, Bluetooth 5.0, Dual-band WiFi

## New USB3.0

2xUSB3.0 + 2xUSB2.0

## USB-C Power

Upgraded Power Supply, More Powerful

# BCM2711B0

## 64-Bit Quad-Core Processor

Cortex-A72  
ARM Architecture

64-bit  
Quad-core

1.5GHz  
Frequency

Faster, more powerful CPU

Provides smooth experience like X86 desktop PC



## 4K Ultra High Definition

## Dual Micro HDMI

Upgrade to dual micro HDMI instead of a full size HDMI

Dual displays, up to 60fps refreshing rate


## Bluetooth 5.0 BLE

## 2.4G / 5G Dual-Band WIFI

Upgraded Bluetooth 5.0 BLE, better performance

Dual-band WIFI, along with the Gigabit Ethernet

Better connectivity, faster and more stable networking



## New USB3.0 Ports

## Faster Data Transmission

2xUSB 3.0 + 2xUSB 2.0

No more trouble when connecting with high speed devices

# Raspberry Pi Versions Comparing

	ZERO	ZEROW/ WH	3A+	3B	3B+	4B
SOC	BCM2835		BCM2837B0			BCM2711B0
CPU	ARM11 Single-core 700MHz		ARM Cortex-A53 Quad-core (3B 1.2GHz, 3A+/3B+ 1.4GHz)			ARM Cortex-A72 Quad-core 1.5GHz
GPU	Broadcom VideoCore IV@400MHz					Broadcom VideoCore IV@500MHz
RAM	512MB		512MB	1GB		Choice of 2GB/4GB/8GB
USB	1x micro USB		1x USB2.0	4x USB2.0		2x USB2.0 + 2x USB3.0
HDMI	Micro HDMI		HDMI			Mini HDMI
Bluetooth	N/A	Bluetooth 4.1	Bluetooth 4.2	Bluetooth 4.1	Bluetooth 4.2	Bluetooth 5.0
WiFi	N/A	802.11 b/g/n	3B: 802.11 b/g/n, others: 802.11 b/g/n/ac 2.4GHz/5GHz dual band			
Ethernet	N/A		100Mbps		300Mbps (USB)	1000Mbps
PoE	N/A				Yes	
Power Input	Micro USB (5V 2.5A)					USB Type-C (5V 3A)
Dimensions	65 × 30 x 5 mm		65 × 56 mm	85 x 56 x 17 mm		



## 2GB/4GB/8GB WHICH SHOULD I CHOOSE?

**2GB**

Suitable for running lots apps while GUI is not required, e.g. robot controller and smart car.

**4GB**

Suitable for graphic task or Internet application, e.g. watching video as normal PC, or deploying a network server.

**8GB**

Suitable for complicate multi-tasking, heavy server workloads e.g. dual display 4K video playing, AI depth vision learning.


The total operational performance of Pi 4B is more than triple the 3B+'s, even the 2GB variant. Larger RAM has minor impact on performance if the RAM is just enough, therefore, we should choose the RAM capacity that best fits the target project. It is unnecessary to always choose the largest RAM.

# Applications

Your Tiny, Dual-Display, Desktop Computer  
...And Robot Brains, Smart Home Hub, Media Center, Game Console...



tiny dual-display desktop (balance work and life)



Raspberry Pi smart robot (try the AI magic)



Raspberry Pi game console (relive retro games)



Study and development (DIY endless possibilities)

Our Team

## O-LEADING *CUSTOMER*

To be *RELIABLE*

Quality first ,  
Customer supreme ,  
Scientifically management ,  
Striving for famous brand



# THE CUSTOMER IS *KING*



To be *VALUABLE*

Science and technology keeps head ,  
Put people first ,  
Be precise and practical ,  
contribute sincerely



## Factory PCB



Automatic vacuum press machine



Drilling Machine



Pattern Plating Machine



Scrubbing Machine



Developing Machine



Routing Machine



High-speed flying probe machine



E-test Machine

## Factory SMT



# HOW O-LEADING MAKE A PROJECT FOR YOU

Hardware Dispenser Application Not

## Automatic Dispenser Application Not


Voltage Table

Volt Pin Number	Description
VDD	Battery Voltage
+3V3	+3.3V
+5V	+5V
USB +5V	USB 5V input
+5V2	Isolated +5V
+12V	12V DC Drive

STM32F072 PinOUT table


Wire Name	Description	DIO	Mode	Note
SHTN_TOF	Shutdown Time of flight sensor	Output	Logic '0' to shutdown	
I2C_SCL_TOF	I2C communication with time of flight sensor	I2C1_SCL		
I2C_SDA_TOF	I2C communication with time of flight sensor	I2C1_SDA		
I2C_SCL_IR	I2C communication with thermopile sensor	I2C2_SCL		
I2C_SDA_IR	I2C communication with thermopile sensor	I2C2_SDA		
RATE_LC	Load cell control pins	Output		
DOUT_LC	Load cell control pins	Output		

**O-LEADING**  
To Be Reliable, To Be Valuable





## HARDWARE schematics

## PCB PRODUCTION COMPONENTS SOURCING



Qty	Value	Device	Parts	Description
4	AK500/2	AK500/2	X1, X2	CONNECTOR
1	AK500/3	AK500/3	X7	CONNECTOR
1	124114	MA04-2	SV2	
1	PPPC04	MA04-2	SV1	8 POS , 4*2 FEMALE PIN HEADE
1	ML10	ML10	SV4	HARTING
1	8MHZ	XTALL CSTCE8M	X5	STCE8M00G52-R0 RESONATOR
1	0R	R-0603	R53	Thick Film Resistors - SMD 0603
2	10R	R-0603	R12, R5	Thick Film Resistors - SMD 0603
8	100R	R-0603	R1, R2	Thick Film Resistors - SMD 0603
1	270R	R-0805	R15	Thick Film Resistors - SMD 0605
1	330R	R-0603	R11	Thick Film Resistors - SMD 0603
9	680R	R-0603	R20, R3	Thick Film Resistors - SMD 0603
17	1k	R-0603	R9, R10	Thick Film Resistors - SMD 0603
2	4.7k	R-0603	R17, R6	Thick Film Resistors - SMD 0603
2	5.1k	R-0603	R18, R1	Thick Film Resistors - SMD 0603
9	10k	R-0603	R16, R3	Thick Film Resistors - SMD 0603
1	100k	R-0603	R20, R7	Thick Film Resistors - SMD 0603



## PCB Assembly MECHANICAL DESIGN

Skyworth 创维

**HAT** 和而泰  
HAT INTELLIGENT CONTROL

dongweikeji  
东威科技

美的 Midea

STAR-NET  
星网锐捷

FORYOU  
ADAYO 华阳集团

**EDIFIER**®

Cultraview 金锐显

3nod 三诺

**T&W**

**TCL**

AcBel 康舒科技  
ACBEL POLYTECH INC.

**Honeywell**

Schneider  
Electric

**ZTE** 中兴

**EMERSON**

**BYD**

**PHILIPS**

**TE**  
connectivity


**VIDEOTON**




CUSTOMER VOICE IS **EXTREMELY IMPORTANT** TO US

订单编号: 49335463501024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)

 **High quality usb power pcb , pcba manufacturer**  
★★★★★  
Fancy has done an excellent job, whenever we write, she answered us within 1 second, O-leading is very perfect with fast delivery, fast logistics, the most important thing is good quality, good packaging, thank you!


[回复该评论](#)

 **oem customized rohs pcb drawing schematic s...**  
★★★★★  
We received the boards, the quality is very good, the price is very reasonable, Fancy is very nice & smart & experienced, the logistics is super fast, I will come to see more in the future.


[回复该评论](#)

订单编号: 49298271001024670


供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)

 **High TG180 FR-4 Circuit HDI PCB 94V0 Board ...**  
★★★★★  
perfect product, perfect PCB supplier!

[回复该评论](#)

 **oem customized rohs pcb drawing schematic s...**  
★★★★★  
Very good and professional PCB product as usual!


[回复该评论](#)


 **Strip LED Aluminum FR-4 lighting PCB board 9...**  
★★★★★  
High quality, fast delivery, good service, competitive price, lucky and happy to purchase from O-leading!

[回复该评论](#)

订单编号: 49822411001024670


供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)

 **High TG180 FR-4 Circuit HDI PCB 94V0 Board ...**  
★★★★★  
This is a very difficult PCB design, but we are lucky to find O-leading to support the PCB for us very good to a PCB supplier.

 **universal FR4 Multilayer PCB washing machine...**  
★★★★★  
Fancy gives us very excellent service, very professional and experienced, O-leading is the best one of our suppliers, very happy to work with them.

订单编号: 49024962001024670


United States  
供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)

 **High quality Keyboard pcb & pcba Factory SMT...**  
★★★★★  
Top quality, it's the right choice to choose O-leading to make the PCB & PCBA

[回复该评论](#)


订单编号: 4093862301024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)

 **Professional Printed Circuit Board Manufactur...**  
★★★★★  
Very high quality PCB products, O-leading is the best PCB supplier that we have ever worked with.

订单编号: 44068794501024670


供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)


 **High TG180 FR-4 Circuit HDI PCB 94V0 Board ...**  
★★★★★  
We bought two batches, one by DHL, the other one by air, good quality and fast delivery!


LISTEN TO **CUSTOMER VOICE**


订单编号: 4090347501024670


供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)


 **Strip LED Aluminum FR-4 lighting PCB board 9...**  
★★★★★  
Very fast delivery! Fantastic, good job!!

 **Professional Printed Circuit Board Manufactur...**  
★★★★★  
Very happy to great support from O-leading, they are not only professional on the PCB, but also provide good PCB products, very good supplier!

 **hot sale rigid-flexible PCB with 0.2mm BGA an...**  
★★★★★  
very professional supplier


 **High Quality custom FPCB/Flex PCB/FPC/Flexi...**  
★★★★★  
Good product



 **OEM ODM PCBA Bluetooth Wireless Marking G...**  
★★★★★  
high soldering quality


 **Electronic parts haptic pcba Circuit Board asse...**  
★★★★★  
Very Good product

订单编号: 37378603001024670

供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)


 **Raspberry pi 0 Zero Raspberry Pi Zero Pi W ver...**  
★★★★★  
Fantastic products!!


 


 **double layer pcb with red S/M and LF-HASL su...**  
★★★★★  
Good!


订单编号: 36919647001024670


供应商服务: 非常满意 (5 stars) 按时发货: 非常满意 (5 stars)


 **AML-S802 Quad-core Android embedded boar...**  
★★★★★  
Good products


 **Fast delivery low cost pcb fabrication O-leadin...**  
★★★★★  
Good supplier


 **Lidar IR Sensor board pcba(H08R6x)**  
★★★★★  
perfect product

 **Customized PCBA design PCB design**  
★★★★★  
perfect

 **Audio Speaker and Headphone Jack (H07R3x)**  
★★★★★  
High quality, good

 **half hole pcb, half hole pcb module, half hole m...**  
★★★★★  
Top half hole pcb supplier, very perfect goods

 **High Quality custom FPCB/Flex PCB/FPC/Flexi...**  
★★★★★  
this rigid-flexible pcb quality is perfect!

 **Electronic parts haptic pcba Circuit Board asse...**  
★★★★★  
Very satisfied with O-leading products and quality, especially their on-time delivery, fantastic!

**Be kind to your client,  
because he has many choices,  
but he chooses you instead.**

# Certifications

O-LEADING *TRAINING*



Keep *LEARNING*

There's a phrase in Buddhism, 'Beginner's mind.'


It's wonderful to have a beginner's mind



WE HAVE A *DREAM*

Keep *RUNNING*

I would like to live to study, and not study to live.

----Bacon









## ZPMV2.E490354 - WIRING, PRINTED - COMPONENT

## Wiring, Printed - Component

See General Information for Wiring, Printed - Component

**O-LEADING SUPPLY CHAIN (HK) CO LTD**

E490354

ROOM 1205, 12/F  
TAI SANG BANK BLDG  
130-132 DES VOEUS ROAD  
CENTRAL, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DSO	Max		Max		Meets UL796	C T	
	Min	Min			Area	Solder	Oper	Flame			
	mm(in)	mm(in)			Diam	Limits	Temp	Class			
Multilayer (mass laminate) printed wiring boards.											
O-LEADING-401	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	130	V-0	-	-
O-LEADING-407	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.7 (0.4)	260	10	130	V-0	All	-
Multilayer printed wiring boards.											
O-LEADING-408	0.125 (0.005)	0.125 (0.005)	12 (0.47) Int:136	DS	50.8 (2.0)	280	20	130	V-0	All	*
Single layer printed wiring boards.											
O-LEADING-002	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	All	-
O-LEADING-003	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	130	V-0	▲	-
O-LEADING-033	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	All	-
O-LEADING-205	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.6 (2.7)	260	10	130	V-0	All	-
O-LEADING-206	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	All	-
O-LEADING-D01	0.14 (0.006)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	All	*
O-LEADING-S01	0.25 (0.010)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	260	4	130	V-0	All	*

## WIRING, PRINTED - COMPONENT | UL Product iQ

<b>O-LEADING-S02</b>	0.2 (0.008)	0.2 (0.008)	17 (0.67)	SS	25.4 (1.0)	260	4	130	HB	▲
<b>O-LEADING-S03</b>	0.25 (0.010)	0.25 (0.010)	34 (1.34)	SS	25.4 (1.0)	260	4	130	V-0	All

\* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2019 UL LLC”

# Process Capability

## PCB Production Capabilities

Layer Count	1Layer-32Layer
Finished copper thickness	1/3oz-12oz
Min Line width/spacing internal	3.0mil/3.0mil
Min Line width/spacing external	4.0mil/4.0mil
Max Aspect Ratio	10:1
Board thickness	0.2mm-5.0mm
Max Panel size(inches)	635*1500mm
Minimum Drilled Hole Size	4mil
Plated Hole Tolerance	+/-3mil
Blind/Buried Vias (All Types)	YES
Via Fill(Conductive,Non-Conductive)	YES
Base Material	FR-4,FR-4high Tg,Halogen free material,Rogers,Aluminium base,Polyimide,Heavy Copper
Surface finishes	HASL,OSP,ENIG,HAL-LF,Immersion silver,Immersion Tin,Gold fingers,Carbon ink

## SMT Production Capabilities

PCB Material	FR-4,CEM-1,CEM-3,Aluminum-based board,FPC
Max PCB size	510x1500mm
Min PCB size	50x50mm
PCB Thickness	0.5mm-4.5mm
Board thickness	0.5-4mm
Min Components size	0201
Standard chip size component	0603 and larger
Component max height	15mm
Min lead pitch	0.3mm
Min BGA ball pitch	0.4mm
Placement precision	+/-0.03mm

## Packaging & Delivery

# Shipping service





Quick Turn Lead Time		
Layer Count:	Lead Tim	Special Requirement
1L/2L	2-3days	24 Hours,48 Hours
4L	3-4days	48 Hours
6L	4-5days	72 Hours
8L	5-6days	NA
10L	6-7days	NA
12L	7-8days	NA
14L	8-9days	NA

Standard Lead Time		
Layer Count:	Sample Lead Time	Volume order lead time
2L	4 days	10 days
4L	5 days	11 days
6L	6 days	12 days
8L	8 days	14 days
10L	10 days	16 days
12L	12 days	18 days
14L	14 days	20 days
16-32L	18 days	24 days

## FAQ

### 1. How do O-Leading ensure quality?

Our high quality standard is achieved with the following.

- 1.1 The process is strictly controlled under ISO 9001:2008 standards.
- 1.2 Extensive use of software in managing the production process
- 1.3 State-of-art testing equipments and tools. E.g. Flying Probe, X-ray Inspection, AOI (Automated Optical Inspector) and ICT (in-circuit testing).
- 1.4.Dedicated quality assurance team with failure case analysis process
- 1.5.Continuous staff training and education

### 2. How do O-Leading keep your price competitive?

Over the last decade, prices of many raw materials (e.g. copper, chemicals) had doubled, tripled or quadrupled; Chinese currency RMB had appreciated 31% over US dollar; And our labor cost also increased significantly.

However, O-Leading have kept our pricing steady. This owns entirely to our innovations in reducing cost, avoiding wastes and improving efficiency. Our prices are very competitive in the industry at the same quality level.

We believe in a win-win partnership with our customers. Our partnership will be mutually beneficial if we can provide you an edgeon cost and quality.

### **3. What kinds of boards can O-Leading process?**

Common FR4, high-TG and halogen-free boards, Rogers, Arlon, Telfon, aluminum/copper-based boards, PI, etc.

### **4. What data are needed for PCB & PCBA production?**

4.1 BOM (Bill of Materials) with reference designators: component description, manufacturer's name and part number.

4.2 PCB Gerber files.

4.3 PCB fabrication drawing and PCBA assembly drawing.

4.4 Test procedures.

4.5 Any mechanical restrictions such as assembly height requirements.

### **5. What's the typical process flow for multi-layer PCB?**

Material cutting → Inner dry film → inner etching → Inner AOI → Multi-bond → Layer stack up Pressing → Drilling → PTH → Panel Plating → Outer Dry Film → Pattern Plating → Outer etching → Outer AOI → Solder Mask → Component Mark → Surface finish → Routing → E/T → Visual Inspection.

### **6. What's the key equipments for HDI manufacturing?**

Key equipment list is as following: Laser drilling machine, Pressing machine, VCP line, Automatic Exposing machine, LDI and etc.

The equipments we have are the best in the industry, laser drilling machines are from Mitsubishi and Hitachi, LDI machines are from Screen(Japan), Automatic Exposing machines are also from Hitachi, all of them make we can meet customer's technical requirements.

### **7. How many types of surface finish O-lead can do?**

O-the leader has the full series of surface finish, such as: ENIG, OSP, LF-HASL, gold plating (soft/hard), immersion silver, Tin, silver plating, immersion tin plating, carbon ink and etc. .. OSP, ENIG, OSP + ENIG commonly used on the HDI, we usually recommend that you use a client or OSP OSP + ENIG if BGA PAD size less than 0.3 mm.

### **8. What's your capability for FPC? Can O-Leading provide SMT service also?**

O-Leading can fabricate FPC from single layer to 8layer, the working panel size can be as large as 2000mm\*240mm, please find the details in the page "Flex Capability"

We also provide SMT one stop service to customer.

### **9. What are the main factors which will affect the price of PCB?**

Material;

Surface finish;

Technology difficulty;

Different quality criteria;

PCB characteristics;

Payment terms;

Different manufacturing countries.

### **10. What's the definition of PCB, PWB and FPC and what's the difference?**

PCB is short for Printed Circuit Board;

PWB is short for Printed Wire Board, same meaning as Printed Circuit Board;

FPC is short for Flexible Printed Board.

### **11. What factors should be considered when choosing the material for a PCB board?**

Below factors should be considered when we choose the material for PCB:

The material's Tg value should be greater than the operation temperature;

Low CTE material has good performance of thermal stability;

Good thermal resistance performance: Normally PCBs are required to resist 250°C for at least 50s.  
Good flatness; In consideration of the electrical properties, low loss/high permittivity material is used on high frequency PCB; Polyimide glass fiber substrate used for flexible PCB; Metal core is used when the product has strict requirement of heat dissipation.

## **12. What's the merits of O-leading's rigid-flex PCB?**

O-leading's rigid-flex PCB has the characters of both FPC and PCB, so it can be used in some special products. Some part is flexible while the other part rigid, it can help save product's interior space, reduce product volume and improve performance.

## **13. How to you make the impedance calculation?**

The impedance control system is done using some test coupons, the SI6000 soft and the CITS 500s equipment from POLAR INSTRUMENTS.

The equipment measures the impedance on a representative track configuration coupon of which the client has given us a determinate value and tolerance.