

Ooooooooooooo

O-Leading PCB PCB PCB PCBA EMS

[illegible]

O

PCB


PCBA

A diagram of a 16-bit register. The first 12 bits are white, and the last 4 bits are orange. The orange bits are labeled "PCB" in blue text.


00000000



WE MAKE YOUR IDEA COME TRUE








PCB

15 YEARS EXPERIENCE




O-LEADING
To Be Reliable, To Be Valuable


BOM

Item	Qty	Reference	Part Description	Manufacturer / Part #
1	1	B1	RECTIFIER, BRIDGE 600V 0.8A	DIODES INC. HD06-T
2	1	CAC1	CAP. 0.1uF 20% 250V/275VAC ECQ-UL	PANASONIC, ECQUAAF104M
3	1	C2	CAP. FILM, 0.22uF 20% 400V	PANASONIC ECQE4224KF
4	1	C3	CAP. 10uF 20% 50V ALUM	RUBYCON 50YXJ10M 5X11
5	1	C6	CAP. 0805 0.1uF 10% 50V X7R	TDK, C2012X7R1H104K
6	1	C7	CAP. 0805 2.2uF 10% 50V X5R	TDK, C2012X5R1H225K
7	1	C8	CAP. 0805 4.7uF 20% 16V X5R	AVX 0805YD475MAT2A
8	2	C10,C11	CAP. 1000uF 20% 35V ELEC	Panasonic EEUF1V102
9	1	C13	CAP. 1210 2.2nF, 5% 630V U2J	Murata, GRM32A7U2J222JW31D
10	1	C20	CAP. 2.2nF 20% 400V, Y5U TYPE "Y1"	VISHAY, 440LD22-R
11	2	C12,C21	CAP. 0805 22pF +/-0.25pF 50V NPO	AVX, 08055A220JAT2A
12	2	C23,C25	CAP. 1210 10uF 20% 35V X5R	Murata, GRM32ER7YA106KA12L
13	1	C24	CAP. 1206 47pF 10% 630V NPO	Murata, GRM31A5C2J470JW01D
14	2	C25,C26	CAP. 2.2nF 20% 300VAC RADIAL	Murata, DE6E3KJ222MN3A
15	1	D1	DIODE, ULTRA FAST RECTIFIER	CENTRAL SEMI, CMR1U-10M
16	1	D2	DIODE, FAST SWITCHING	DIODES INC., BAV20W-7-F
17	1	D5	DIODE, SUPER BARRIER RECIFIER 20A	DIODES INC., SBR20A200CTB
18	1	D8	DIODE, FAST SWITCHING	DIODES INC., 1N4148W-7-F
19	1	F1	FUSE, 3.15A, FAST ACTING	COOPER BUSSMAN, SS-5F-3.15A


SCH



O-LEADING
To Be Reliable, To Be Valuable



PCBA



PCB





Factory PCB



Automatic vacuum press machine



Drilling Machine



Pattern Plating Machine



Scrubbing Machine



Developing Machine



Routing Machine



High-speed flying probe machine



E-test Machine

Factory SMT







No. SZXEC1900530401

Date: 30 Mar 2019

Page 1 of 6

O-LEADING SUPPLY CHAIN (HK) CO., LIMITED

1313, FLOOR 13, FORTUNE BUILDING, DANSHUI TOWN, HUIYANG DISTRICT, HUIZHOU, GUANGDONG, CHINA

The following sample(s) was/were submitted and identified on behalf of the clients as : OSP

SGS Job No. : RP19-005089 - SZ

Date of Sample Received : 22 Mar 2019

Testing Period : 22 Mar 2019 - 30 Mar 2019

Test Requested : Selected test(s) as requested by client.

Test Method : Please refer to next page(s).

Test Results : Please refer to next page(s).

Conclusion : Based on the performed tests on submitted sample(s), the results of Lead, Mercury, Cadmium, Hexavalent chromium, Polybrominated biphenyls (PBBs), Polybrominated diphenyl ethers (PDBEs) and Phthalates such as Bis(2-ethylhexyl) phthalate (DEHP), Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP), and Diisobutyl phthalate (DIBP) comply with the limits as set by RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU.

Signed for and on behalf of
SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Tina Fan
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed on the back, available on request or accessible at <http://www.spa.com/terms-and-conditions> and, for electronic formal documents, subject to Terms and Conditions for Electronic Documents at <http://www.spa.com/terms-and-conditions/terms-e-document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is deemed to have read, understood and accepted the terms and conditions of the document and to have agreed to follow the Client's instructions, if any. The Company's sole responsibility is to its Client and the document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced or transmitted in any form or by any means electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without the prior written permission of the Company. Any unauthorized use or reproduction of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the samples tested.

SGS S&P, No.4, Jiangyin Industrial Park, No.430, Jiang Road, Suzhou, Jiangsu Province, China 215129 | (86-756) 25326888 | (86-756) 83106190 | www.sgsgroup.com.cn
中国·苏州·工业园区娄葑镇430号江泾工业园4号SGS大楼 邮编 215129 | (86-756) 25326888 | (86-756) 83106190 | www.sgsgroup.com.cn
e: sgs.china@sgs.com

Member of the SGS Group (SGS SA)



No. SZXEC1900530401

Date: 30 Mar 2019

Page 2 of 6

Test Results :

Test Part Description:

Specimen No.	SGS Sample ID	Description
SN1	SZX19-005304.001	Green™PCB

Remarks :

(1) $1 \text{ mg/kg} = 1 \text{ ppm} = 0.0001\%$

(2) MDL = Method Detection Limit

(3) ND = Not Detected (< MDL)

(4) "-" = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method : With reference to IEC 62321-4:2013+A1:2017, IEC62321-5:2013, IEC62321-7-2:2017, IEC 62321-6:2015 and IEC62321-8:2017, analyzed by ICP-OES, UV-Vis and GC-MS.

Test Item(s)	Limit	Unit	MDL	Q27
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	8
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (Cr(VI))	1,000	mg/kg	8	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tri bromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND
Dibromodiphenyl ether	-	mg/kg	5	ND
Tri bromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed and available on request or accessible at <http://www.kals.com/termsandconditions.aspx>, subject to Terms and Conditions for Electronic Documents at <http://www.kals.com/termsandconditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is deemed to have accepted the terms and conditions of the document and the Company's General Conditions of Service and Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced without the prior written consent of the Company. Any unauthorized reproduction, alteration, forgery or misuse, or the appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the samples tested.

SQS Bldg. M-1, JCNH Industrial Park, No.400, Shua Road, Beidian, Langgang District, Shenzhen, China 518129 t (86-755)25328888 f (86-755)83106190 www.sqsgroup.com.cn
中国·深圳·龙岗区田面华路430号江田工业园4楼SQS大厦 邮编:518129 t (86-755)25328888 f (86-755)83106190 e sqs.china@sqsg.com

Member of the SGS Group (SGS SA)



ZPMV2.E490354 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

O-LEADING SUPPLY CHAIN (HK) CO LTD

E490354

ROOM 1205, 12/F
TAI SANG BANK BLDG
130-132 DES VOEUS ROAD
CENTRAL, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max		Max		Meets UL796 Class	C T DSR	C I
	Min	Min			Area	Solder	Oper	Flame			
	mm(in)	mm(in)			Diam	Limits	Temp	Temp			
Multilayer (mass laminate) printed wiring boards.											
O-LEADING-401	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	130	V-0	-	-
O-LEADING-407	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.7 (0.4)	260	10	130	V-0	All	-
Multilayer printed wiring boards.											
O-LEADING-408	0.125 (0.005)	0.125 (0.005)	12 (0.47) Int:136	DS	50.8 (2.0)	280	20	130	V-0	All	*
Single layer printed wiring boards.											
O-LEADING-002	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	All	-
O-LEADING-003	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	130	V-0	▲	-
O-LEADING-033	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	All	-
O-LEADING-205	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.6 (2.7)	260	10	130	V-0	All	-
O-LEADING-206	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	All	-
O-LEADING-D01	0.14 (0.006)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	All	*
O-LEADING-S01	0.25 (0.010)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	260	4	130	V-0	All	*

WIRING, PRINTED - COMPONENT | UL Product iQ

O-LEADING-S02	0.2 (0.008)	0.2 (0.008)	17 (0.67)	SS	25.4 (1.0)	260	4	130	HB	▲	*
O-LEADING-S03	0.25 (0.010)	0.25 (0.010)	34 (1.34)	SS	25.4 (1.0)	260	4	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2019 UL LLC”

PCB SMT

PCB		SMT	
PCB	1~32	PCB	FR-4 CEM-1 CEM-3
PCB	1 / 3oz-12oz		
PCB/PCB	3.0mil / 3.0mil	PCB	510x460mm
PCB/PCB	4.0mil / 4.0mil	PCB	50x50mm
PCB	10~1	PCB	0.5mm-4.5mm
PCB	0.2mm-5.0mm	PCB	0.5-4mm
PCB	635 * 1500mm	PCB	0201
PCB	4mil	PCB	0603
Plated Hole Tolerance	+/- 3mil	PCB	15mm
Blind / Buried Vias	PCB	PCB	0.3mm
Via Fill	PCB	PCB BGA	0.4mm
PCB	FR-4 FR-4high Tg	PCB	+/- 0.03mm
PCB	HASL OSP ENIG HAL-LF		

Shipping service

Shipping service



Quick Turn Lead Time		
Layer Count:	Lead Tim	Special Requirement
1L/2L	2-3days	24 Hours,48 Hours
4L	3-4days	48 Hours
6L	4-5days	72 Hours
8L	5-6days	NA
10L	6-7days	NA
12L	7-8days	NA
14L	8-9days	NA

Standard Lead Time		
Layer Count:	Sample Lead Time	Volume order lead time
2L	4 days	10 days
4L	5 days	11 days
6L	6 days	12 days
8L	8 days	14 days
10L	10 days	16 days
12L	12 days	18 days
14L	14 days	20 days
16-32L	18 days	24 days



1. O

Our company is a professional PCB manufacturer.

1.1 Our company is ISO 9001:2008 certified.

1.2 Our company is a professional PCB manufacturer.

1.3 Our company is a professional PCB manufacturer. X-ray AOI, ICT, etc.

1.4 Our company is a professional PCB manufacturer.

1.5 Our company is a professional PCB manufacturer.

2. O

Our company is a professional PCB manufacturer. 10 years of experience, 2003-2023, 4 years of experience, 31 years of experience.

Our company is a professional PCB manufacturer. Our company is a professional PCB manufacturer. Our company is a professional PCB manufacturer.

Our company is a professional PCB manufacturer. Win-Win, etc.

3. O-Leading

Our company is a professional PCB manufacturer. FR4, TG, etc./PI, etc.

4. PCB/PCBA

4.1 BOM

4.2 PCB Gerber

4.3 PCB PCBA

4.4

4.5

5. PCB

→ → AOI → → PTH → → → → AOI → → → E / T →

6. HDI

VCP LDI

LDI Screen

7. O

O- ENIG OSP LF-HASL / HDI OSP ENIG OSP + ENIG BGAPAD 0.3 mm OSP OSP + ENIG

8. FPC O-Leading SMT

O-Leading FPC 8 2000mm * 240mm SMT

9. PCB

;
;
;
PCB
;

10. PCB PWB FPC

PCB Printed Circuit Board
PWB Printed Wire Board Printed Circuit Board
FPC Flexible Printed Board

11. PCB

PCB
Tg
CTE
PCB 50 250°C
PCB / PCB

12. O rIgid-flex PCB

O-leading PCB FPC PCB

13.

SI6000 POLAR INSTRUMENTS CITS 500s

