O-leading[illegible]

O-Leading[illegible]PCB[illegible]PCB[illegible]PCB[illegible]PCBA[illegible]EMS[illegible]HDI PCB[illegible]PCB[illegible]PCB[illegible]PCB[illegible]

[illegible]O[illegible]

[illegible]O-leading[illegible]PCB[illegible]PCBA[illegible]

[illegible]**FR-4[illegible]FPC[illegible]**

[illegible]

O-LEADING
To Be Reliable, To Be Valuable

Fast delivery and top quality Rigid Flexible PCB

O-LEADING
To Be Reliable, To Be Valuable

O-LEADING
To Be Reliable, To Be Valuable

O-LEADING
To Be Reliable, To Be Valuable

O-LEADING
To Be Reliable, To Be Valuable

Production Process

18 years experience in one-stop PCB and PCBA,we can make your idea come true,

CONSUMER ELECTRONICS
AUTOMOTIVE ELECTRONICS
INDUSTRIAL CONTROL
INTELLECTUALIZED HOUSEHOLD CONTROL
OTHER
18%
INTELLECTUALIZED HOUSEHOLD CONTROL
30%
CONSUMER ELECTRONICS
20%
AUTOMOTIVE ELECTRONICS
12%
OTHER
20%
INDUSTRIAL CONTROL


Product types
2%
13%
85%
FR-4 PCB
MC PCB
rigid-flexible PCB


Product layers
1L
2L
4L
6L
>8L
>8L
9%
1L
13%
6L
25%
2L
30%
4L
23%

□□□□□□□□

O-LEADING
To Be Reliable, To Be Valuable

Factory PCB

Automatic vacuum press machine

Drilling Machine

Pattern Plating Machine

Scrubbing Machine

Developing Machine

Routing Machine

High-speed flying probe machine

E-test Machine

Factory SMT

O-LEADING
To Be Reliable, To Be Valuable

合作伙伴 Customers

Skyworth 创维
HST 和布泰 HST INTELLIGENT CONTROL
dongweikeji 东威科技
美的 Midea
STAR-NET 星网锐捷
FORYOU ADAYO 华阳集团
EDIFIER
Cultraview 金锐显
3nod三诺
T&W
TCL
AcBel 康舒科技 ACBEL POLYTECH INC.
Honeywell
Schneider Electric
ZTE中兴
EMERSON
BYD
PHILIPS
TE connectivity
VIDEOTON

CICC CERTIFICATION
嘉泰认证

CICC INSPECTION CERTIFICATION

QUALITY MANAGEMENT SYSTEM CERTIFICATE

Certificate No: 18118Q10347R0S

We hereby certify that

O-LEADING SUPPLY CHAIN(HK) CO.,LIMITED

Credit No: 61691591-000-07-18-7

Registration Add: FLAT/RM 1205 12/F TAI SANG BANK BUILDING 130-132 DES VOEUS ROAD CENTRAL HK

Business Add: 1313, Floor 13, Fortune Building, Danshui Town, Huiyang District, Huizhou, Guangdong, China

Has implemented and maintains a **Quality Management System**

Which fulfils the requirements of the following standards

GB/T19001-2016 idt ISO9001:2015

Scope of certification

Sales of printed circuit boards

Initial Issuance period: February 27, 2018

Renewal date: April 22, 2019

This certificate is valid during: April 22, 2019 ~ February 26, 2021

This certificate is invalid without CICC qualified label in the following period

First supervision and audit		Second supervision and audit	Qualified mark

CICC CERTIFICATION IAF CNAS

CICC CERTIFICATION
嘉泰认证

CICC INSPECTION CERTIFICATION

质量管理体系认证证书

证书号：18118Q10347R0S

兹证明

诚领供应链（香港）有限公司

统一社会信用代码：61691591-000-07-18-7

注册地址：香港中環德輔道中130-132號大生銀行大廈1205室

经营地址：广东惠州惠阳淡水南亨西路财富大厦13楼1313

建立的质量管理体系符合

GB/T19001-2016 idt ISO9001:2015 质量标准适用条款的要求

认证范围

印刷线路板的销售

初次获证日期：2018年02月27日

换证日期：2019年04月22日

证书有效期：自2019年04月22日至2021年02月26日

在下列期限内，未经CICC贴防合格标贴，本证书无效

第一次监审		第二次监审	贴标处

本证书认证范围不包括未获得有效的国家规定的相关行政许可、资质许可的产品/服务范围；

本证书通过CICC定期监督审核保持，与年度《保持认证通知书》共同方为有效；

本证书信息可在国家认监委网站：www.cnca.gov.cn及CICC网站www.cicc-cqc.com查询。

CICC CERTIFICATION IAF CNAS

SGS

Test Report No. SZXEC1900530401 Date: 30 Mar 2019 Page 1 of 6

O-LEADING SUPPLY CHAIN (HK) CO.,LIMITED

1313,FLOOR 13, FORTUNE BUILDING, DANSHUI TOWN, HUIYANG DISTRICT, HUIZHOU, GUANGDONG, CHINA

The following sample(s) was/were submitted and identified on behalf of the clients as : OSP

SGS Job No. :	RP19-005089 - SZ
Date of Sample Received :	22 Mar 2019
Testing Period :	22 Mar 2019 - 30 Mar 2019
Test Requested :	Selected test(s) as requested by client.
Test Method :	Please refer to next page(s).
Test Results :	Please refer to next page(s).
Conclusion :	Based on the performed tests on submitted sample(s), the results of Lead, Mercury, Cadmium, Hexavalent chromium, Polybrominated biphenyls (PBBs), Polybrominated diphenyl ethers (PBDEs) and Phthalates such as Bis(2-ethylhexyl) phthalate (DEHP) , Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP) , and Diisobutyl phthalate (DIBP) comply with the limits as set by RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU.

Signed for and on behalf of
SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Tina

Tina Fan
Approved Signatory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
| SGS Bldg. No.2, Jianghai Industrial Park, No.68, Jihua Road, Bantian, Longgang District, Shenzhen, China 518129 | t (86 - 755) 25328888 | f (86 - 755) 83106190 | www.sgsgroup.com.cn
中国 · 深圳 · 龙岗区坂田吉华路430号江灏工业园4栋SGS大楼 邮编: 518129 | t (86 - 755) 25328888 | f (86 - 755) 83106190 | e sgs.china@sgs.com
Member of the SGS Group (SGS SA)

SGS

Test Report No. SZXEC1900530401 Date: 30 Mar 2019 Page 2 of 6

Test Results :

Test Part Description :

Specimen No.	SGS Sample ID	Description
SN1	SZX19-005304.001	Green"PCB"

Remarks :

(1) 1 mg/kg = 1 ppm = 0.0001%
(2) MDL = Method Detection Limit
(3) ND = Not Detected (< MDL)
(4) "-" = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method : With reference to IEC 62321-4:2013+A1:2017, IEC62321-5:2013, IEC62321-7-2:2017, IEC 62321-6:2015 and IEC62321-8:2017, analyzed by ICP-OES, UV-Vis and GC-MS.

Test item(s)	Limit	Unit	MDL	001
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	8
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (Cr(VI))	1,000	mg/kg	8	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tribromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND
Dibromodiphenyl ether	-	mg/kg	5	ND
Tribromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
| SGS Bldg. No.2, Jianghai Industrial Park, No.68, Jihua Road, Bantian, Longgang District, Shenzhen, China 518129 | t (86 - 755) 25328888 | f (86 - 755) 83106190 | www.sgsgroup.com.cn
中国 · 深圳 · 龙岗区坂田吉华路430号江灏工业园4栋SGS大楼 邮编: 518129 | t (86 - 755) 25328888 | f (86 - 755) 83106190 | e sgs.china@sgs.com
Member of the SGS Group (SGS SA)

UL Product iQ™

ZPMV2.E490354 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

O-LEADING SUPPLY CHAIN (HK) CO LTD E490354
ROOM 1205, 12/F
TAI SANG BANK BLDG
130-132 DES VOEUS ROAD
CENTRAL, HONG KONG

Type	Cond Width Min mm(in)	Cond Width Min Edge mm(in)	Cond Thk mic(mil)	SS/ DS/ DSO	Max Area Diam mm(in)	Solder Limits C	Solder Limits sec	Max Oper Temp C	Flame Class	Meets UL796 DSR	CTI
Multilayer (mass laminate) printed wiring boards.											
O-LEADING-401	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	130	V-0	-	-
O-LEADING-407	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.7 (0.4)	260	10	130	V-0	All	-
Multilayer printed wiring boards.											
O-LEADING-408	0.125 (0.005)	0.125 (0.005)	12 (0.47) Int:136	DS	50.8 (2.0)	280	20	130	V-0	All	*
Single layer printed wiring boards.											
O-LEADING-002	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	All	-
O-LEADING-003	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	130	V-0	▲	-
O-LEADING-033	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	All	-
O-LEADING-205	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.6 (2.7)	260	10	130	V-0	All	-
O-LEADING-206	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	All	-
O-LEADING-D01	0.14 (0.006)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	All	*
O-LEADING-S01	0.25 (0.010)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	260	4	130	V-0	All	*

WIRING, PRINTED - COMPONENT | UL Product iQ

O-LEADING-S02	0.2 (0.008)	0.2 (0.008)	17 (0.67)	SS	25.4 (1.0)	260	4	130	HB	▲	*
O-LEADING-S03	0.25 (0.010)	0.25 (0.010)	34 (1.34)	SS	25.4 (1.0)	260	4	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2019 UL LLC”

□□□□□□

PCB□□□□	
□□□□□	1Layer-32Layer
□□□□□	1 / 3oz-12oz
□□□□/□□□□	3.0mil / 3.0mil
□□□□/□□□□	4.0mil / 4.0mil
□□□□□□□□	10□1
□□	0.2mm□5.0mm
□□□□□□□□□□□□□□	635 * 1500mm
□□□□□□□□□	4mil
PIated□□□□	+/- 3mil
BIind / Buried Vias□AII□□□□	□□
Via Fill□□□□□□□□□□□	□□
□□	FR-4□FR-4high Tg□□
□□□□□	HASL□OSP□ENIG□HAL-LF□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

SMT□□□□

PCB□□	FR-4□CEM-1□CEM-3□□□□□□□□□□□□□□
□□PCB□□□	510x460mm
□□PCB□□□	50x50mm
PCB□□□	0.5mm□4.5mm
□□	0.5□4mm
□□□□□□□□□□□□□	0201
□□□□□□□□□□□□□□□□□	0603□□
□□□□□□□□□□□□□□	15mm
□□□□□□□□□	0.3mm
□□BGA□□□□□□	0.4mm
□□□□	+/- 0.03mm

□□□□□

Shipping service

DHL WORLDWIDE EXPRESS TNT FedEx Express UPS

Quick Turn Lead Time		
Layer Count:	Lead Tim	Special Requirement
1L/2L	2-3days	24 Hours,48 Hours
4L	3-4days	48 Hours
6L	4-5days	72 Hours
8L	5-6days	NA
10L	6-7days	NA
12L	7-8days	NA
14L	8-9days	NA

Standard Lead Time		
Layer Count:	Sample Lead Time	Volume order lead time
2L	4 days	10 days
4L	5 days	11 days
6L	6 days	12 days
8L	8 days	14 days
10L	10 days	16 days
12L	12 days	18 days
14L	14 days	20 days
16-32L	18 days	24 days

□□□□□□

1. O□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□
1.1□□□□□ISO 9001□2008□□□□□□□□□□□□□□□□
1.2□□□□□□□□□□□□□□□□□□□□□
1.3□□□□□□□□□□□□□□□□□□□□□□□□□X□□□AOI□□□□□□□□□□□□□□□ICT□□□□□□□□
1.4□□□□□□□□□□□□□□□□□□□□
1.5□□□□□□□□□□□□□□□□□□

2. O-Leading□□□□□□□□□□□□□□□□□□
□□10□□□□□□□□□□□□□□□□□□□□□2□□3□□4□□□□□□□□□□□□□□□□□□□□31□□□□□□□□□□□□□□□□□□□□
□□□□O-Leading□□
□□□□□□□□□
□□□

3. O-Leading□□□□□□□□□□□□□□□
□□□□FR4□□TG□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□/□□□□□□□□PI□□

4. PCB□□□PCBA□□□□□□□□□□□□□□□□□

4.1 BOM[illegible]
4.2 PCB[illegible]
4.3 PCB[illegible]PCBA[illegible]
4.4[illegible]
4.5[illegible]

5.[illegible]PCB[illegible]

[illegible]→[illegible]→[illegible]→[illegible]AOI→[illegible]→[illegible]→[illegible]→PTH→[illegible]→[illegible]→[illegible]→[illegible]→[illegible]AOI→[illegible]→[illegible]→[illegible]→[illegible]→E / T→[illegible]

6. HDI[illegible]

[illegible]VCP[illegible]LDI[illegible]
[illegible]LDI[illegible]

7. O-[illegible]

O-[illegible]ENIG[illegible]OSP[illegible]LF-HASL[illegible]/[illegible] OSI[illegible]ENIG[illegible]OSP + ENIG[illegible]HDI[illegible]BGAPAD[illegible]0.3 mm[illegible]OSP OSP + ENIG[illegible]

8. FPC[illegible] O-Leading[illegible]SMT[illegible]

O-Leading[illegible]FPC[illegible]1[illegible]8[illegible]2000mm * 240mm[illegible]SMT[illegible]

9. PCB[illegible]

[illegible];
[illegible];
[illegible];
[illegible];
PCB[illegible];
[illegible];
[illegible]

10. PCB[illegible]PWB[illegible]FPC[illegible]

PCB[illegible]
PWB[illegible]Printed Wire Board[illegible]Printed Circuit Board[illegible]
FPC[illegible]

11. PCB[illegible]

PCB[illegible]
[illegible]Tg[illegible]
[illegible]CTE[illegible]
[illegible]PCB[illegible]250℃[illegible]50[illegible]
[illegible];[illegible]PCB[illegible]/[illegible]PCB[illegible]

12. O-leading[illegible]PCB[illegible]

O-leading[illegible]PCB[illegible]FPC[illegible]PCB[illegible]

13.[illegible]

[illegible]POLAR INSTRUMENTS[illegible]SI6000 soft[illegible]CITS 500s[illegible]
[illegible]