

0

10 PCB - PCB MCPCB
 - 24 S / S 48-96 4-8

.025 AVG .020 ..

25 /

PCB

PCB P / N	PCB S1550 TG 150
	2L
	FR-4 TG150
THK	1.60mm
THK	1 / 1oz
	0.50mm
	29
w / s	10/8
Y / N Tol	N
	Au 0.05-0.10UM
	/ N / A
	X mm 21.5 Y mm 60.3
ion	X mm 108; Y mm 138.1; UPS 8
	N
	CNC



www.o-leading.com

PCB

.



www.o-leading.com









201726 201VZL430354 - Wiring, Printed - Component



ONLINE CERTIFICATIONS DIRECTORY

ZPMV2.E490354
Wiring, Printed - Component

For enhanced search functionality, please visit UL's [Global Databases](#).
Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Components](#)

O-LEADING SUPPLY CHAIN CO LIMITED

Fortune Building, Nanheng West Road

Room 1313

Huizhou, Guangdong 516211, CHINA

E490354

Typc	Cond Width			SS/ DS/	Area Diam	Solder		Temp	Flame	RoHS	C
	Min	Min	Cond			Di	Di				
Hub/Bayer (mass laminate) printed wiring boards.											
D-LEADING-401											
	0.2 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	230	V-0	-	-
D-LEADING-402											
	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.2 (0.4)	260	10	170	V-0	NI	-
Hub/Bayer printed wiring boards.											
D-LEADING-408											
	0.225 (0.009)	0.125 (0.005)	12 (0.47) 31:1.35	DS	50.8 (2.0)	260	20	230	V-0	NI	-
Single layer printed wiring boards.											
D-LEADING-002											
	0.76 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	NI	-
D-LEADING-003											
	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	230	V-0	▲	-
D-LEADING-033											
	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	NI	-
D-LEADING-205											
	0.2 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.6 (2.7)	260	10	230	V-0	NI	-
D-LEADING-206											
	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	NI	-

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.
Last updated on 2017-01-27

Questions? [Print this page](#) [Terms of Use](#) [Page Top](#)

[http://www.ul.com/ULProductDetail.aspx?ProductID=201VZL430354&ProductType=Wiring,Printed-Component&Category=19](#)

SGS

Test Report

No. CANEC1805164701

Date: 03 Apr 2018

Page 2 of 8

Test Results:

Test Part Description:

Specimen No. **SGS Sample ID** **Description**
SN1 CAN18-051647.001 Green "PCB"

Remarks:

- (1) 1 mg/kg = 1 ppm = 0.0001%
- (2) MDL = Method Detection Limit
- (3) ND = Not Detected (< MDL)
- (4) "-" = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method: With reference to IEC 62321-4:2014+A1:2017, IEC 62321-5:2013, IEC 62321-7:2017, IEC 62321-8:2015 and IEC 62321-9:2017, analyzed by ICP-OES, UV-Vis and GC-MS.

Test Item(s)	Limit	Unit	MDL	Det
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	9
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (CrVI)	1,000	mg/kg	8	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tribromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND
Dibromodiphenyl ether	-	mg/kg	5	ND
Tribromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND



SGS is pleased to announce the successful completion of the RoHS testing of the Green PCB. The test results are as follows: The Green PCB is RoHS compliant. The test results are as follows: The Green PCB is RoHS compliant. The test results are as follows: The Green PCB is RoHS compliant.

SGS Testing Services, Ltd. (SGS) is a member of the SGS Group (SGS SA).
Address: Guangzhou, China
Tel: +86 20 3813 1000

4. PCB

Gerber 274-X Cam350 CAD Protel 99se PADS DXP Eagle

5. PCB

→ AOI → PTH → → → → E / T →