

O-LEADING


O-Leading PCB 專業, PCB 設計 PCB 製造 (PCBA) 專業 EMS 專業 專業 專業 專業 專業 HDI PCB, 專業 PCB, 專業-專業 PCB 專業 專業 PCB 專業 專業. 專業 專業 專業 專業 專業 專業 專業 專業 專業 專業. ([PCB 專業](#))

專業 專業 專業 專業 專業, 專業 專業 專業 專業 專業 專業. 專業 專業 專業 專業 專業 專業 專業 O-LEADING 專業 專業.


專業 O-leading 專業 專業 專業 專業 專業 專業, 專業 專業 專業 專業 專業 專業 專業 PCB & PCBA 專業 專業 專業 專業 專業 專業. ([OEM PCB 專業 專業](#))

專業 專業

專業	專業 專業 (專業)	專業	O- 專業
專業 專業	FR-4, 專業, 專業, 專業 專業 專業	專業 專業	0.5 專業 -5 專業
專業 專業 專業	0.2mm	專業 專業 專業	0.2mm
專業 專業	專業 專業 / 專業 專業, OSP, 專業 HASL	專業 專業	0.1-5mm
專業 專業 專業	專業, 專業 專業, 專業, 專業	專業	專業 專業 PCB
專業	ISO9001, UL, RoHS, SGS	Q / CTN	專業 專業 專業
專業	0.01kg -5kg	MOQ	10 專業
專業	, 專業, 專業, 專業, black.yellow	專業 專業 專業	0.2m
專業 專業	pcb 專業 專業 pcha 專業	專業	\$ 0.1- \$ 10
design 專業	專業ent 專業 專業	專業	0.01m3-10m3



www.o-leading.com



www.o-leading.com



Factory PCB



Automatic vacuum press machine



Drilling Machine



Pattern Plating Machine



Scrubbing Machine



Developing Machine



Routing Machine



High-speed flying probe machine



E-test Machine

Factory SMT







No. SZXEC1900530401

Date: 30 Mar 2019

Page 1 of 6

O-LEADING SUPPLY CHAIN (HK) CO., LIMITED

1313, FLOOR 13, FORTUNE BUILDING, DANSHUI TOWN, HUIYANG DISTRICT, HUIZHOU, GUANGDONG, CHINA

The following sample(s) was/were submitted and identified on behalf of the clients as : OSP

SGS Job No. : RP19-005089 - SZ

Date of Sample Received : 22 Mar 2019

Testing Period : 22 Mar 2019 - 30 Mar 2019

Test Requested : Selected test(s) as requested by client.

Test Method : Please refer to next page(s).

Test Results : Please refer to next page(s).

Conclusion : Based on the performed tests on submitted sample(s), the results of Lead, Mercury, Cadmium, Hexavalent chromium, Polybrominated biphenyls (PBBs), Polybrominated diphenyl ethers (PDBEs) and Phthalates such as Bis(2-ethylhexyl) phthalate (DEHP), Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP), and Diisobutyl phthalate (DIBP) comply with the limits as set by RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU.

Signed for and on behalf of
SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Tina Fan
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed on the back, available on request or accessible at <http://www.spa.com/terms-and-conditions> and, for electronic formal documents, subject to Terms and Conditions for Electronic Documents at <http://www.spa.com/terms-and-conditions/terms-e-document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is deemed to have read, understood and accepted the Terms and Conditions of Service and the Terms and Conditions for Electronic Documents. The Client's instructions, if any. The Company's sole responsibility is to its Client and the document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced or transmitted in any form or by any means electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system. Any appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the samples tested.

SGS 303g No.4, Jiangnan Industrial Park, No.438, Jiao Road, Santan, Longgang District, Shenzhen, China 518129 t: (86-755) 25326888 f: (86-755) 83106190 www.sgsigroup.com.cn
中国·深圳·龙岗区松田金牛路438号江楠工业园4楼SGS大楼 邮编: 518129 t: (86-755) 25326888 f: (86-755) 83106190 e: sgs.china@sgs.com.cn

Member of the SGS Group (SGS SA)



No. SZXEC1900530401

Date: 30 Mar 2019

Page 2 of 6

Test Results :

Test Part Description:

Specimen No.	SGS Sample ID	Description
SN1	SZX19-005304.001	Green™PCB

Remarks :

(1) $1 \text{ mg/kg} = 1 \text{ ppm} = 0.0001\%$

(2) MDL = Method Detection Limit

(3) ND = Not Detected (< MDL)

(4) "-" = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method : With reference to IEC 62321-4:2013+A1:2017, IEC62321-5:2013, IEC62321-7-2:2017, IEC 62321-6:2015 and IEC62321-8:2017, analyzed by ICP-OES, UV-Vis and GC-MS.



SGS B&B, Ltd., Jiahe Industrial Park, No.430, Jiahe Road, Bantian, Longgang District, Shenzhen, China 518129 t: (86-755) 25328888 f: (86-755) 83106190 www.sgsigroup.com.cn
中国·深圳·龙岗区坂田雪莲路430号江嘉工业园4楼SGS大厦 邮编: 518129 t: (86-755) 25328888 f: (86-755) 83106190 e: sgs.china@sgs.com

Member of the SGS Group (SGS SA)



ZPMV2.E490354 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

O-LEADING SUPPLY CHAIN (HK) CO LTD

E490354

ROOM 1205, 12/F
TAI SANG BANK BLDG
130-132 DES VOEUS ROAD
CENTRAL, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max		Max		Meets UL796	C T				
	Min	Min			Area Diam	Solder Limits	Oper Temp	Flame						
	mm(in)	mm(in)			mm(in)	C	sec	C	Class	DSR	I			
Multilayer (mass laminate) printed wiring boards.														
O-LEADING-401	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	130	V-0	-	-			
O-LEADING-407	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.7 (0.4)	260	10	130	V-0	All	-			
Multilayer printed wiring boards.														
O-LEADING-408	0.125 (0.005)	0.125 (0.005)	12 (0.47) Int:136	DS	50.8 (2.0)	280	20	130	V-0	All	*			
Single layer printed wiring boards.														
O-LEADING-002	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	All	-			
O-LEADING-003	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	130	V-0	▲	-			
O-LEADING-033	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	All	-			
O-LEADING-205	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.6 (2.7)	260	10	130	V-0	All	-			
O-LEADING-206	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	All	-			
O-LEADING-D01	0.14 (0.006)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	All	*			
O-LEADING-S01	0.25 (0.010)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	260	4	130	V-0	All	*			

WIRING, PRINTED - COMPONENT | UL Product iQ

O-LEADING-S02	0.2 (0.008)	0.2 (0.008)	17 (0.67)	SS	25.4 (1.0)	260	4	130	HB	▲	*
O-LEADING-S03	0.25 (0.010)	0.25 (0.010)	34 (1.34)	SS	25.4 (1.0)	260	4	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2019 UL LLC”

Shipping service



Quick Turn Lead Time		
Layer Count:	Lead Tim	Special Requirement
1L/2L	2-3days	24 Hours,48 Hours
4L	3-4days	48 Hours
6L	4-5days	72 Hours
8L	5-6days	NA
10L	6-7days	NA
12L	7-8days	NA
14L	8-9days	NA

Standard Lead Time		
Layer Count:	Sample Lead Time	Volume order lead time
2L	4 days	10 days
4L	5 days	11 days
6L	6 days	12 days
8L	8 days	14 days
10L	10 days	16 days
12L	12 days	18 days
14L	14 days	20 days
16-32L	18 days	24 days



PCB 規格

層數 : 1Layer-32Layer
 銅厚 : 1 / 3oz-12oz
 線寬 / 線距 : 3.0mil / 3.0mil
 鑽孔 / 微孔 : 4.0mil / 4.0mil
 孔徑 : 10 : 1
 厚度 : 0.2mm-5.0mm
 板面尺寸 (mm) : 635 * 1500mm
 表面鍍層 : 4mil
 Plated 厚度 : +/- 3mil
 Blind / Buried Vias (All 規格) : 可
 材料 (FR-4, FR-4high Tg) : 可
 材料 : FR-4, FR-4high Tg.Halogen free material, Rogers, Aluminium base, 其他材料
 鍍層 : HASL, OSP, ENIG, HAL-LF, 其他, 鍍金, 鍍銀, 鍍銅

SMT 規格

PCB 材料 : FR-4, CEM-1, CEM-3, 銅箔 銅 箔

銅 PCB 材料 : 510x460mm

銅 PCB 材料 : 50x50mm

PCB 材料 0.5mm-4.5mm

銅 箔 0.5-4mm

銅 箔 材料 : 0201

銅 箔 材料 : 0603 箔

銅 箔 材料 15mm

銅 箔 材料 : 0.3mm

銅 BGA 材料 : 0.4mm

銅 箔 : +/- 0.03mm