

## O 板

提供 10 种 板 板 PCB 板。板 板, 板, 板 PCB, 板 PCB 板 MCPCB 板。板 板 板 板 板 板 板 板 板。24 板 板 S / S, 48-96 板 板 板 4-8 板。

板 板 PCB 板 板 板

板 板 板 .025 AVG, .020 板 板 板 板 板

板 板 板 板, 25 PCS / bag, 板 板 板 板 板 板 板 板 板

板 板 板 板 板 板 板

## 板 板

- PCB 板 板 板 板 板

PCB P / N	O- 板
板 板	2L
板	FR-4
板 thk	1.60mm
板 thk	1/1 板
板 板 板 板	0.2MM
板 板 ( )	30
板 板 板. Y / N ( % )	板

**O-LEADING**  
To Be Reliable, To Be Valuable



[www.o-leading.com](http://www.o-leading.com)









201726 201VZL430354 - Wiring, Printed - Component



ZPMV2.E490354  
Wiring, Printed - Component

For enhanced search functionality, please visit [ul.com/Products/Database](http://ul.com/Products/Database).  
Click on a product designation for complete information.

Page Bottom

Wiring, Printed - Component

See General Information for Wiring, Printed - Components

O-LEADING SUPPLY CHAIN CO LIMITED 4190354

Fortune Building, Nanheng West Road  
Room 1313  
Huizhou, Guangdong 516211, CHINA

	Cond Width			SS/ DS/	Area Diam	Solder		Dper		Flame	RoHS	C
	Min	Max	Min			Max	Temp	Class				
Min	Edge	Thk	DS/	Thk	Temp	Class	DSR	I				
<b>Hullayer (mass laminate) printed wiring boards.</b>												
<b>O-LEADING-401</b>												
0.2 (0.004)	0.3 (0.012)	34 (1.34)	D6	12.7 (0.5)	260	10	130	V-0	-	-	-	-
<b>O-LEADING-407</b>												
0.08 (0.003)	0.2 (0.008)	17 (0.67)	D5	9.2 (0.4)	260	10	130	V-0	NI	-	-	-
<b>Hullayer printed wiring boards.</b>												
<b>O-LEADING-408</b>												
0.125 (0.005)	0.125 (0.005)	12 (0.47) 31-135	D6	50.8 (2.0)	260	20	130	V-0	NI	-	-	-
<b>Single layer printed wiring boards.</b>												
<b>O-LEADING-002</b>												
0.76 (0.015)	1.14 (0.045)	34 (1.34)	S5	19.1 (0.8)	260	10	105	V-0	NI	-	-	-
<b>O-LEADING-003</b>												
0.38 (0.015)	1.14 (0.045)	34 (1.34)	S5	19.1 (0.8)	260	10	130	V-0	▲	-	-	-
<b>O-LEADING-033</b>												
0.15 (0.006)	0.3 (0.012)	34 (1.34)	S5	25.4 (1.0)	260	10	120	V-0	NI	-	-	-
<b>O-LEADING-205</b>												
0.1 (0.004)	0.3 (0.012)	34 (1.34)	D6	69.6 (2.7)	260	10	130	V-0	NI	-	-	-
<b>O-LEADING-206</b>												
0.15 (0.006)	0.33 (0.013)	17 (0.67)	D5	69.6 (2.7)	260	10	130	V-0	NI	-	-	-

\* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.  
Last updated on 2017-01-27

Questions? Print this page Terms of Use Page Top

<http://www.ul.com/Products/Database/Products/201VZL430354> - Wiring, Printed - Component



Test Report

No. CANEC1805164701

Date: 03 Apr 2018

Page 2 of 8

Test Results:

Test Part Description:

Specimen No. **SGS Sample ID** **Description**  
SNI CAN18-051647.001 Green "PCB"

Remarks:

- (1) 1 mg/kg = 1 ppm = 0.0001%
- (2) MDL = Method Detection Limit
- (3) ND = Not Detected (< MDL)
- (4) "r" = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method: With reference to IEC 62321-4:2014+A1:2017, IEC62321-5:2013, IEC62321-7-2:2017, IEC 62321-6:2015 and IEC62321-8:2017, analyzed by ICP-OES, UV-Vis and GC-MS.

Test Item(s)	Limit	Unit	MDL	Det
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	9
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (CrVI)	1,000	mg/kg	8	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tribromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND
Dibromodiphenyl ether	-	mg/kg	5	ND
Tribromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND



SGS is pleased to announce the launch of its new online platform for the provision of test results. The platform is designed to provide a secure and efficient way for clients to access their test results. The platform is available in English, French, German, Italian, Japanese, Korean, Spanish, and Chinese. For more information, please contact your local SGS office or visit [www.sgslab.com](http://www.sgslab.com).

Member of the SGS Group (SGL SA)

00 00 00	16 0 00 OEM pcb 00 0000
00 00 00	7-12 0



1. O-Leading 0 000 000 00000? [00000-PCB 00000 00](#)

0000 0000 0000 0000 00 000000.

1. 000000 ISO 9001 : 2008 0000 00 000000 000000.

00 00 0000 00000000 000000 00

3. 0000 0000 00 0 00. 0 : 0000 0000, X-ray 00, AOI (Automated Optical Inspector) 0 ICT (in-circuit testing).

4. 00 00 00 000000 00 00 00 00 0

5. 00 00 00 0 00

2. O-Leading 0 0000 00 00000 000000?

00 10 0 00 00 0000 (0 : 00, 00 00)0 0000 0 0, 0 0 00 0 00 0000000. 00 00 00000 00 00000 31 % 00000000. 00 0000 00 00000000. 0000 O-Leading 0 000000 00000000. 00 00 00, 00 00 0 0000 000000 0000 0000 00 00000. 0000 0000 0000 00 00000 00000 00000.

0000 00000 00 0000000 00000. 0000 0000000 0000 0 0000 0000 0000000 00 0000 0 00000.

3. O-Leading 0 00 0000 0000 00 0 0 00000?

00 FR4, 0 TG 0 0 0000 00, Rogers, Arlon, Telfon, 00000 / 00 00 00, PI 0

4. PCB 0000 0000 000000 000000?

Gerber 274-X 圖檔 圖檔 圖檔 圖 圖 圖檔. 圖 Cam350, CAD, Protel 99se, PADS, DXP 圖 Eagle 圖 圖 圖 圖

5. 圖 PCB 圖檔 圖檔 圖 圖檔?

圖 圖 → 圖 圖 圖 → 圖 圖 → 圖 AOI → 圖 圖 → 圖 圖 圖 圖 → 圖 → PTH → 圖 圖 → 圖 圖 圖 → 圖 圖 → 圖  
圖 → 圖 AOI → 圖 圖 → 圖 圖 圖 → 圖 圖 → 圖 → E / T → 圖 圖.