

PCB

PCB Specifications

Material	FR-4, GFR	Thickness	0.5oz ~ 5oz
Min. Drill Size	0.2mm	Min. Hole Size	0.2mm
Surface Finish	OSP, HASL	Panel Size	0.1-5mm
Components	LED, Resistor, Capacitor, IC	PCB Type	Single / Double PCB
Standards	ISO9001, UL, RoHS, SGS	Q / CTN	10PCS-100PCS
Weight	0.01kg ~ 5kg	MOQ	10pcs
PCB Type	Single PCB, Double PCB, Flex PCB	Min. Thickness	0.2mm
Color	Green, Yellow, Blue, Red	Price	\$ 0.1 - \$ 10
Lead Time	3-7 days	Quantity	0.01m3-10m3

PCB & PCB

PCB Type	16 OEM PCB
Lead Time	7-12 days

PCB

16 OEM PCB

Item	2014		2015 ~ 2016		2017 ~ 2018	
	Value	Value	Value	Value	Value	Value
Drill Size (mm)	32	42	38	44	42	48
Drill Size / Hole Size (µm)	50/50	40/45	40/45	40/40	35/40	35/35
Min. Drill Size (mm)	0.15	0.10	0.15	0.10	0.15	0.10
PTH	14 : 1	16 : 1	16 : 1	18 : 1	18 : 1	20 : 1
N + C + N	4 + C + 4	5 + C + 5	5 + C + 5	6 + C + 6	5 + C + 5	6 + C + 6
Drill Size / Hole Size	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6
Min. Drill Size (µm)	50	40	40	30	40	30
Min. Hole Size (µm)	75	65	65	50	50	40
Material	FR4, Megtron, Nelco, Rogers, Heavy Copper					
PCB Type	Single / Double PCB					
Surface Finish	HASL, ENIG, OSP, Immersion Silver, Electroless Nickel, Electroless Nickel Immersion Gold, Electroless Nickel Immersion Silver					

