

O-leading PCB PCB PCB PCB.

10 PCB PCB PCB PCB. PCB - PCB, PCB PCB, PCB PCB, PCB PCB MCPCB. PCB PCB PCB PCB PCB PCB
 PCB PCB - 24 PCB S / S, 48-96 PCB PCB 4-8 PCB.

(led pcb board PCB PCB PCB PCB)

PCB PCB PCB .025 AVG, .020 MIN .. PCB PCB PCB PCB PCB PCB

PCB PCB PCB PCB, 25 PCB / bag, PCB PCB PCB, PCB PCB PCB PCB PCB

PCB PCB PCB PCB PCB PCB : PCB PCB PCB PCB PCB

PCB PCB

PCB P / N	S1550 TG 150 PCB PCB PCB PCB PCB
PCB PCB	2L
PCB	FR-4 TG150 PCB PCB
PCB thk	1.60mm
PCB thk	1 / 1oz
PCB PCB PCB PCB	0.50mm
PCB PCB (PCB)	29
PCB w / s	10 PCB 8 PCB
PCB PCB PCB. Y / N (Tol %)	PCB
PCB PCB	ENIG Au : 0.05-0.10UM
PCB PCB PCB PCB	PCB PCB / N / A
PCB PCB PCB	PCB X (mm) : 21.5; PCB Y (mm) : 60.3
PCB PCB	PCB X (mm) : 108; PCB Y (mm) : 138.1; UPS PCB : 8
PCB : PCB PCB PCB	PCB
PCB / PCB	CN PCB

•





www.o-leading.com

-
-
- [PCB 0000](#)







201726 201VZL430354 - Wiring, Printed - Component



ZPMV2.E490354
Wiring, Printed - Component

For enhanced search functionality, please visit UL's [online family of databases](#).
Click on a product designation for complete information.

Page Bottom

Wiring, Printed - Component

See General Information for Wiring, Printed - Components

O-LEADING SUPPLY CHAIN CO LIMITED

Fortune Building, Nanheng West Road
Room 1313
Huizhou, Guangdong 516211, CHINA

E490354

	Cond Width			SS/ DS/	Area Diam	Solder		Temp		Flame	RoHS	C
	Min	Max	Min			Max	Class	DSR				
Typ	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I	
Hullayer (mass laminate) printed wiring boards.												
O-LEADING-401												
	0.2 (0.004)	0.3 (0.012)	34 (1.34)	D6	12.7 (0.5)	260	10	130	V-0	-	-	
O-LEADING-407												
	0.08 (0.003)	0.2 (0.008)	17 (0.67)	D5	9.2 (0.4)	260	10	170	V-0	NI	-	
Hullayer printed wiring boards.												
O-LEADING-408												
	0.125 (0.005)	0.125 (0.005)	12 (0.47) min:1.25	D6	50.8 (2.0)	260	20	130	V-0	NI	*	
Single layer printed wiring boards.												
O-LEADING-002												
	0.76 (0.015)	1.14 (0.045)	34 (1.34)	S5	19.1 (0.8)	260	10	105	V-0	NI	-	
O-LEADING-003												
	0.38 (0.015)	1.14 (0.045)	34 (1.34)	S5	19.1 (0.8)	260	10	130	V-0	▲	-	
O-LEADING-033												
	0.15 (0.006)	0.3 (0.012)	34 (1.34)	S5	25.4 (1.0)	260	10	120	V-0	NI	-	
O-LEADING-205												
	0.1 (0.004)	0.3 (0.012)	34 (1.34)	D6	69.6 (2.7)	260	10	130	V-0	NI	-	
O-LEADING-206												
	0.15 (0.006)	0.33 (0.013)	17 (0.67)	D5	69.6 (2.7)	260	10	130	V-0	NI	-	

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.
Last updated on 2017-01-27

Questions? [Print this page](#) [Terms of Use](#) [Page Top](#)

http://www.ul.com/onlinecertifications/UL60716RMS/ewg/zpmv2.e490354/wiring-printed-component/10



Test Report

No. CANEC1805164701

Date: 03 Apr 2018

Page 2 of 8

Test Results:

Test Part Description:

Specimen No. **SGS Sample ID Description**
SN1 CAN18-051647.001 Green PCB*

Remarks:

- (1) 1 mg/kg = 1 ppm = 0.0001%
- (2) MDL = Method Detection Limit
- (3) ND = Not Detected (< MDL)
- (4) * = Not Regulated

RoHS Directive (EU) 2015/863 amending Annex II to Directive 2011/65/EU

Test Method: With reference to IEC 62321-4:2014+A1:2017, IEC62321-5:2013, IEC62321-7-2:2017, IEC 62321-6:2015 and IEC62321-8:2017, analyzed by ICP-OES, UV-Vis and GC-MS.

Test Item(s)	Limit	Unit	MDL	Det
Cadmium (Cd)	100	mg/kg	2	ND
Lead (Pb)	1,000	mg/kg	2	9
Mercury (Hg)	1,000	mg/kg	2	ND
Hexavalent Chromium (CrVI)	1,000	mg/kg	8	ND
Sum of PBBs	1,000	mg/kg	-	ND
Monobromobiphenyl	-	mg/kg	5	ND
Dibromobiphenyl	-	mg/kg	5	ND
Tribromobiphenyl	-	mg/kg	5	ND
Tetrabromobiphenyl	-	mg/kg	5	ND
Pentabromobiphenyl	-	mg/kg	5	ND
Hexabromobiphenyl	-	mg/kg	5	ND
Heptabromobiphenyl	-	mg/kg	5	ND
Octabromobiphenyl	-	mg/kg	5	ND
Nonabromobiphenyl	-	mg/kg	5	ND
Decabromobiphenyl	-	mg/kg	5	ND
Sum of PBDEs	1,000	mg/kg	-	ND
Monobromodiphenyl ether	-	mg/kg	5	ND
Dibromodiphenyl ether	-	mg/kg	5	ND
Tribromodiphenyl ether	-	mg/kg	5	ND
Tetrabromodiphenyl ether	-	mg/kg	5	ND
Pentabromodiphenyl ether	-	mg/kg	5	ND



SGS is pleased to announce the launch of its new online reporting system for RoHS testing. This system is designed to provide a more efficient and user-friendly experience for our clients. The new system will allow clients to upload test results directly to the online reporting system, which will automatically generate a report. This report will be available to the client within 24 hours of the test. The new system will also allow clients to track the status of their test results in real-time. This system is a significant step forward for SGS in providing our clients with the most efficient and user-friendly testing experience. For more information, please contact your account manager or visit our website at [www.sgs.com](#).

Member of the SGS Group (SGS SA)

□□ & □□

□□ □□ □□	16 □ □□ OEM pcb □□ □□ □□
□□ □□ □□	7-12 □



□□□□ □□

1. O-Leading□ □□□ □□ □□□□□?

□□□ □□□ □□□ □□ □□ □□□□□.

1. □ □□□□□ ISO 9001 : 2008 □□□ □□ □□□ □□□□□.

2. □□ □□ □□□□□ □□□□□□ □□□□ □□

3.State-of-art □□□ □□ □ □□. □ : □□□ □□□, X □ □□, AOI (□□ □□ □□□) □ ICT (□□ □ □□□).

4. □□ □□ □□ □□□□□ □□ □ □□ □□ □□ □

5. □□□□ □□ □□ □ □□

2. O-Leading□ □□ □□□□ □□□ □□□□□?

□□ 10 □ □□ □□ □□□ (□ : □□, □□ □□) □□□ □ □, □ □ □□ □ □ □□□□□□. □□ □□ □□□□ □□ □□ 31 % □□□ □□□. □□ □□□□ □□ □ □□□□□. □□□□ □□□□ □□□□□□□□. □□ □□ □□, □□□□ □□ □ □□□ □□□ □□ □□□□ □□ □□□□. □□□□ □□□□ □□ □□□□ □□ □□□□ □□ □□□□ □□ □□□□.

□□□□ □□□□ □□ □□□□ □□□ □□ □ □ □□□ □□□□□ □□ □□□ □ □□□□.

3. O-Leading □□□□□□ □□ □□□ □□ □ □□□□□?

□□□□ FR4, □ TG □ □□□ □□ □□, Rogers, Arlon, Telfon, □□□□ / □□ □□ □□, PI □

4. PCB □□□ □□□ □□□□ □□□□□?

Gerber 274-X □□□□ □□□□ □□□□ □□ □□ □□□□. □□ Cam350, CAD, Protel 99se, PADS, DXP □ Eagle□ □□ □ □ □□□

□.

5. □□ PCB□ □□□□ □□ □□□ □□□□□?

□□ □□ → □□ □□ □ → □□ □□ → □□ AOI → □□ □□ → □□ → □□ → □□ → PTH → □□ → □□ □□ □ → □□ □□ → □□ □□ → □□ AOI
→ □□ □□□ → □□ □□ → □□ □□ → □□□□ → E / T → □□ □□.