

PCB

PCB Specifications

Material	FR-4, 2000	Thickness	0.5oz ~ 5oz
Min. Thickness	0.2mm	Min. Drill	0.2mm
Surface Finish	OSP, HASL	Panel Size	0.1-5mm
Lighting	LED, UV, IR, Blue	Material	FR-4 PCB
Certification	ISO9001, UL, RoHS, SGS	Q / CTN	10PCS-100PCS
Weight	0.01kg ~ 5kg	MOQ	10pcs
Min. Thickness	0.2mm	Min. Drill	0.2mm
Color	Yellow	Price	\$ 0.1 - \$ 10
Lead Time	3-10 days	Lead Time	3-10 days


PCB & PCB


16 PCB OEM pcb	7-12 days
----------------	-----------

PCB

16 PCB OEM pcb

	2014		2015 ~ 2016		2017 ~ 2018	
	mm	mm	mm	mm	mm	mm
Thickness	32	42	38	44	42	48
Thickness / (mm)	50/50	40/45	40/45	40/40	35/40	35/35
Thickness (mm)	0.15	0.10	0.15	0.10	0.15	0.10
PTH	14 : 1	16 : 1	16 : 1	18 : 1	18 : 1	20 : 1
N + C + N	4 + C + 4	5 + C + 5	5 + C + 5	6 + C + 6	5 + C + 5	6 + C + 6
Thickness	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6	5 + 2 + 5	6 + 2 + 6
Thickness	-	-	-	-	-	-
Min. Thickness (mm)	50	40	40	30	40	30
Min. Thickness (mm)	75	65	65	50	50	40
Thickness	-	-	-	-	-	-
Material	FR4, Megtron, Nelco, Rogers, Heavy Copper					
Thickness PCB	-	-	-	-	-	-
Thickness	HASL, ENIG, OSP, UV, IR, Blue, LED, UV, IR, Blue, LED, UV, IR, Blue					





[pcb 16 pin](#), [pcb 16 pin in china](#)