

# O-Leading PCB 專業 PCB 製造商

O-Lead PCB 專業, PCB 專業 PCB 製造商 (PCBA) 專業 EMS 專業 專業 專業 專業 專業 專業 專業 HDI PCB, 專業 PCB, Rigid-Flexible PCB 專業 專業 專業 PCB 專業 專業 專業 專業. 專業 專業 專業 專業 專業 專業 專業. [專業 專業 專業 專業 專業](#)

專業 專業 專業 專業 專業 專業 專業 專業 : 專業 專業, 專業 O- 專業 專業 專業.

專業 PCB 專業 PCBA 專業 專業 專業 專業 專業 專業.

專業 10 專業 專業 專業 專業 PCB 專業 專業. 專業 專業 - 專業, 專業 PCB, 專業 PCB 專業 MCPCB. 專業 48-96 專業 HRS 專業 專業 4-8 專業 4-8 專業 專業 專業 專業 專業 專業 專業.

專業 專業 專業 專業 .025 AVG, .020 min .. 專業 專業 專業 專業 專業.

專業 專業 專業 專業, 25 專業 / 專業 專業, 專業 專業 專業, 專業 專業 專業 專業 專業.

## 專業 專業

專業 專業 專業


專業	Guang Dong, China (專業)	專業	o-leading.
專業 專業	專業 專業 PCB 專業 專業 PCBA 專業 專業	專業 專業	FR-4, 專業 專業
專業 專業	專業 專業, OSP, 專業 專業 HASL.	專業 專業	0.5oz-5oz.
專業	專業, 專業, 專業, 專業	專業. 專業	0.2mm.
專業 專業	LED, 專業 專業, 專業, 專業	專業. 專業 專業	0.2mm.
專業	專業 專業 PCB	專業 專業	0.1-5mm.
專業	ISO9001, UL, RoHS, SGS.	專業	0.01m3-10m3.
專業	\$ 0.1- \$ 10.	專業	0.01kg -5kg.
design 專業	專業 專業 專業	Q / CTN.	10pcs-100pcs.
MOQ	10pcs.		


專業 專業

### 16 專業 專業 OEM PCB 專業 專業

專業	2014 專業		2015 ~ 2016.		2017 ~ 2018.	
	專業	專業	專業	專業	專業	專業
專業 專業	32.	42.	38.	44.	42.	48.
專業 專業 / 專業 (µm)	50/50.	40/45.	40/45.	40/40.	35/40.	35/35.
Min Drill Hole. 專業 (mm)	0.15.	0.10.	0.15.	0.10.	0.15.	0.10.
專業 專業	14 : 1.	16 : 1.	16 : 1.	18 : 1.	18 : 1.	20 : 1.
N + C + N.	4 + C + 4.	5 + C + 5.	5 + C + 5.	6 + C + 6.	5 + C + 5.	6 + C + 6.

□□ □□□ □□ □□	5 + 2 + 5.	6 + 2 + 6.	5 + 2 + 5.	6 + 2 + 6.	5 + 2 + 5.	6 + 2 + 6.
□□□□ □□ □□	□	-	□	-	□	-
□□. □□ □□ (□□ □□) (μm)	50	40.	40.	30.	40.	30.
□□. □□□□ □□ □□ (μm)	75.	65.	65.	50	50	40.
uried on □□ / □□ □ □□	□	-	□	-	□	-
□□	FR4, Megtron, Nelco, Rogers, □□ □□ □					
□□ □□□□ PCB.	□	-	□	-	□	-
□□ □□	□□ HASL, ENIG, OSP, □□ □□, □□ □□, □□□□ □□, □□ □□□□ □□, □□□□ □□ □□ □□, □□ □□ □□□□ □□ □□□□, □□ □□					





[www.o-leading.com](http://www.o-leading.com)

PCB, LED PCB





---

Factory PCB

---



Automatic vacuum press machine



Drilling Machine



Pattern Plating Machine



Scrubbing Machine



Developing Machine



Routing Machine



High-speed flying probe machine



E-test Machine

---

Factory SMT

---





CICC INSPECTION CERTIFICATION



**嘉泰认证**

**QUALITY MANAGEMENT SYSTEM CERTIFICATE**

Certificate No: 18118Q10347R05

**We hereby certify that**

**O-LEADING SUPPLY CHAIN(HK) CO.,LIMITED**

Credit No: 61691591-000-07-18-7

Registration Add: FLAT/RM 1205 12/F TAI SANG BANK BUILDING 130-132 DES VOEUS ROAD CENTRAL HK

Business Add: 1213, Floor 13, Fortune Building, Danshui Town, Huiyang District, Huizhou, Guangdong, China

Has implemented and maintains a **Quality Management System** Which fulfills the requirements of the following standards  
GB/T19001-2016 idt ISO9001:2015

**Scope of certification**  
Sales of printed circuit boards

Initial issuance period: February 27, 2018  
Renewal date: April 22, 2019  
This certificate is valid during: April 22, 2019 - February 26, 2021  
This certificate is invalid without CICC qualified label in the following period

First supervision and audit	Second supervision and audit	Qualified mark
-----------------------------	------------------------------	----------------

The certification registration number does not include those production stages which fail to be covered by the relevant effective administrative procedures and qualification procedures stipulated by the state. The effectiveness of this certificate shall be restricted to those activities which are covered by the certification. The actual information of this certification can be searched on the internet of CICC www.cicc.com.cn. For the sake of clarity see also the note.






CICC INSPECTION CERTIFICATION



**嘉泰认证**

**质量管理体系认证证书**

证书号: 18118Q10347R05

**兹证明**

**诚领供应链(香港)有限公司**

统一社会信用代码: 61691591-000-07-18-7  
注册地址: 香港中環德輔道中130-132號大生銀行大廈1205室  
经营地址: 广东惠州惠阳淡水南亨西路财富大厦13楼1313

**建立的质量管理体系符合**  
GB/T19001-2016 idt ISO9001:2015 质量标准适用条款的要求

**认证范围**  
印刷线路板的销售

初次获证日期: 2018年02月27日  
换证日期: 2019年04月22日  
证书有效期: 自2019年04月22日至2021年02月26日  
在下列期限内, 未经CICC黏贴合格标贴, 本证书无效

第一次复审	第二次复审	黏贴处
-------	-------	-----

本证书认证范围不包括未取得有效的国家规定的行政许可、资质许可的产品/服务范围; 本证书通过CICC定期监督审核保持, 与年度《保持认证通知书》共同方为有效; 本证书信息可在国家认监委网站: www.cnca.gov.cn及CICC网站www.cicc.com.cn查询。










# ZPMV2.E490354 - WIRING, PRINTED - COMPONENT

## Wiring, Printed - Component

See General Information for Wiring, Printed - Component

**O-LEADING SUPPLY CHAIN (HK) CO LTD**  
 ROOM 1205, 12/F  
 TAI SANG BANK BLDG  
 130-132 DES VOEUS ROAD  
 CENTRAL, HONG KONG

E490354

Type	Cond Width		Cond Thk	SS/ DS/ DSO	Max	Max		Meets	C		
	Min	Edge			Area	Solder	Oper			Flame	
	mm(in)	mm(in)	mic(mil)		Diam	Limits	Temp	Class	UL796	T	
<b>Multilayer (mass laminate) printed wiring boards.</b>											
<b>O-LEADING-401</b>	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	12.7 (0.5)	260	10	130	V-0	-	
<b>O-LEADING-407</b>	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	9.7 (0.4)	260	10	130	V-0	All	
<b>Multilayer printed wiring boards.</b>											
<b>O-LEADING-408</b>	0.125 (0.005)	0.125 (0.005)	12 (0.47) Int:136	DS	50.8 (2.0)	280	20	130	V-0	All	*
<b>Single layer printed wiring boards.</b>											
<b>O-LEADING-002</b>	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	105	V-0	All	-
<b>O-LEADING-003</b>	0.38 (0.015)	1.14 (0.045)	34 (1.34)	SS	19.1 (0.8)	260	10	130	V-0	▲	-
<b>O-LEADING-033</b>	0.15 (0.006)	0.3 (0.012)	34 (1.34)	SS	25.4 (1.0)	260	10	120	V-0	All	-
<b>O-LEADING-205</b>	0.1 (0.004)	0.3 (0.012)	34 (1.34)	DS	69.6 (2.7)	260	10	130	V-0	All	-
<b>O-LEADING-206</b>	0.15 (0.006)	0.33 (0.013)	17 (0.67)	DS	69.6 (2.7)	260	10	130	V-0	All	-
<b>O-LEADING-D01</b>	0.14 (0.006)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	All	*
<b>O-LEADING-S01</b>	0.25 (0.010)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	260	4	130	V-0	All	*

WIRING, PRINTED - COMPONENT | UL Product iQ

<b>O-LEADING-S02</b>	0.2 (0.008)	0.2 (0.008)	17 (0.67)	SS	25.4 (1.0)	260	4	130	HB	▲	*
<b>O-LEADING-S03</b>	0.25 (0.010)	0.25 (0.010)	34 (1.34)	SS	25.4 (1.0)	260	4	130	V-0	All	*

\* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

并不是所有出现在本数据库中的公司名称和产品都满足了UL跟踪检验服务的要求。只有带有UL标志的产品，才应该被视为经过UL认证，并满足UL跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.经 UL 允许从在线认证目录转载“声明必须出现在所提取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2019 UL LLC”



# Shipping service



### Quick Turn Lead Time

Layer Count:	Lead Tim	Special Requirement
1L/2L	2-3days	24 Hours,48 Hours
4L	3-4days	48 Hours
6L	4-5days	72 Hours
8L	5-6days	NA
10L	6-7days	NA
12L	7-8days	NA
14L	8-9days	NA

### Standard Lead Time

Layer Count:	Sample Lead Time	Volume order lead time
2L	4 days	10 days
4L	5 days	11 days
6L	6 days	12 days
8L	8 days	14 days
10L	10 days	16 days
12L	12 days	18 days
14L	14 days	20 days
16-32L	18 days	24 days



### PCB 规格

层数 : 1Layer-32layer.

重量 : 1 / 3oz-12oz.

铜厚 / 铜厚 : 3.0mil / 3.0mil

铜厚 / 铜厚 : 4.0mil / 4.0mil

铜厚 : 10 : 1.

厚度 : 0.2mm-5.0mm.

板面尺寸 (mm) : 635 \* 1500mm

最小孔径 : 4mil.

孔径公差 : +/- 3mil.

盲孔 / 微孔 (All) : 可

VIA 形式 (通孔, 盲孔) : 可

基材 : FR-4, FR-4High TG.Halogen 阻燃, 环氧, 陶瓷填充, 金属填充,

特殊材料

表面处理 : HASL, OSP, ENIG, HAL-LF, LMMersion 可,Immersion tin, 可, 可

### SMT 规格

PCB 材料 : FR-4, CEM-1, CEM-3, 銅箔 銅 箔

銅 PCB 尺寸 : 510x460mm

銅 PCB 尺寸 : 50x50mm.

PCB 厚度 : 0.5mm-4.5mm

銅 箔 : 0.5-4mm.

銅 箔 銅 箔 : 0201.

銅 箔 銅 箔 銅 箔 : 0603 銅 箔

銅 箔 銅 箔 : 15mm

銅 箔 銅 箔 : 0.3mm.

銅 BGA 銅 箔 : 0.4mm.

銅 箔 : +/- 0.03mm.