

PCB

PCB Specifications

Material	FR-4, FR-4 (UL)	Thickness	0.5 - 5oz
Min. Thickness	0.2mm	Min. Drill	0.2mm
Surface Finish	OSP, HASL	Panel Size	0.1-5mm
Applications	LED, Power, Industrial, Medical	Material	FR-4 PCB
Certification	ISO9001, UL, RoHS, SGS	Q / CTN	10PCS-100PCS
Weight	0.01kg ~ 5kg	MOQ	10pcs
Min. Drill	0.2mm	Min. Drill	0.2mm
Color	Yellow	Price	\$ 0.1 - \$ 10
Lead Time	7-12 weeks	Lead Time	0.01m3-10m3

PCB & PCB

16 PCB OEM PCB	7-12 weeks
----------------	------------

PCB

16 PCB OEM PCB

	2014		2015 ~ 2016		2017 ~ 2018	
	Min. Drill	Min. Drill	Min. Drill	Min. Drill	Min. Drill	Min. Drill
Min. Drill (mm)	0.15	0.10	0.15	0.10	0.15	0.10
PTH	14 : 1	16 : 1	16 : 1	18 : 1	18 : 1	20 : 1
N + C + N	4 + C + 4	5 + C + 5	5 + C + 5	6 + C + 6	5 + C + 5	6 + C + 6
Min. Drill (mm)	50	40	40	30	40	30
Min. Drill (mm)	75	65	65	50	50	40
Material	FR4, Megtron, Nelco, Rogers, Heavy Copper					
Surface Finish	HASL, ENIG, OSP, Immersion Silver, Immersion Gold, Electroless Nickel, Electroless Nickel Immersion Gold, Electroless Nickel Immersion Silver					

