

Product Description:

Quick Details

Place of Origin:	Guang dong, China (Mainland)	Brand Name:	O-Leading	Model Number:	power bank pcb assembly pcba manufacturer
Base Material:	FR-4,,Aluminum	Copper Thickness:	0.5oz-5oz	Board Thickness:	0.1-5mm
Min. Hole Size:	0.2mm	Min. Line Width:	0.2mm	Min. Line Spacing:	0.2mm
Surface Finishing:	immersion gold ,OSP,lead free HASL	color:	blue ,red ,green,black,yellow	price:	\$0.1-\$10
applicable to:	led,mobile phone,air conditioners,washing machines	character:	Industrial Control pcb	size:	0.01m3-10m3
certificates:	ISO9001,UL,RoHS,SGS	Q/CTN:	10PCS-100PCS	desigh type:	client requirement
weight:	0.01kg -5kg	MOQ:	10pcs		

Packaging & Delivery

Packaging Details:	16 years professional OEM pcb board manufacturer
Delivery Detail:	7-12days

Product Description

16 years professional OEM pcb board manufacture

item	2014		2015~2016		2017~2018	
	Volume	Sample	Volume	Sample	Volume	Sample
Layer count	32	42	38	44	42	48
Min Line/space (μm)	50/50	40/45	40/45	40/40	35/40	35/35
Min drill hole diameter (mm)	0.15	0.10	0.15	0.10	0.15	0.10
Aspect ratio of PTH	14:1	16:1	16:1	18:1	18:1	20:1
N+C+N	4+C+4	5+C+5	5+C+5	6+C+6	5+C+5	6+C+6
Any layer interconnection	5+2+5	6+2+6	5+2+5	6+2+6	5+2+5	6+2+6
Plate filling via	YES	--	YES	--	YES	--
Min. core thickness (exclude copper) (μm)	50	40	40	30	40	30
Min. Laser Drill diameter (μm)	75	65	65	50	50	40
Via on buried hole/stacked via	YES	--	YES	--	YES	--
Material	FR4, Megtron, Nelco, Rogers, Heavy Copper, etc.					
Embedded capacitor PCB	YES	--	YES	--	YES	--
Surface Process	Lead-free HASL, ENIG, OSP, Immersion silver, Immersion tin, Flash gold, Gold finger plating, Selective hard gold plating, Peelable solder mask, Carbon ink					

